

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

APPLICATOR PARTS LIST				TYPE			AMPLIVAR RING		AMP INCORPORATED WITH HARRISBURG, PENNA. TRIM			
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA		TERMINALS		
1	WIRE CRIMPER 453917-3	1	58021-7	42				TO APPLY TERMINAL		60319-		
2	INS. CRIMPER	1	465589-2	43						60321-		
3	ANVIL	1	465284-1	44				WIRE SIZE	CRIMP HEIGHT	485070-		
4	ANVIL SPACER			45	Spacer - STRIPPER	2	377629					
5	SHEAR BLADE	1	465233-5	46	Tubing Stop	1	811923-2					
6	REAR SHEAR PLATE	1	385013-4	47								
7	SHEAR BLADE SPACER	2	374083	48								
8	FRONT SHEAR PLATE	1	371832	49	Hold down (Blade Mount)	1	811065-1					
9	REAR ANVIL SPACER PLT.			50				CRIMP	SIZE	TYPE	FEED	
10	FRONT ANVIL SPACER PLT.			51				WIRE	.090	FRW	.898	
11	TOOL SPACER	1	371354	52				INSUL.	.155	FRW		
12	CRIMP SPACER	1	370873	53				SEMI Overlap				
13	FRONT STRIP GUIDE	1	472438-9	54				INSULATION RANGE	WIRE RANGE			
14	REAR STRIP GUIDE	1	472438-0	55				.100 - .110	23-19 Magnet			
15	RAM	1	471911	57				EXPLODED VIEW		A-6000 A-6000-3		
16	TOOL HOLDER			58				REMARKS:				
17	ADJ. CRIMP MOUNT Assembly	1	465392-1	59								
18	ADJ. BLOCK			60								
19	APPLICATOR MOUNT	1	570656	61								
20	BASE PLATE			62								
21	BASE BLOCK			63								
22	STRIP GUIDE PLATE			64	MATCH FEED	1	692462					
23	ANVIL HOLDER	1	370526	65	TENSION ADJ. PLATE	1	374979					
24	AUX. ANVIL HOLDER	1	377515	MISCELLANEOUS								
25	STRIPPER & Wire Trimmer	1	811265-2	66	Air Blast Assembly	1	455350-2					
26	STRIPPER MOUNT	2	370660	67	ELBOW	1	22317-3					
27	RETAINER PLATE	2	372251	68	COPPER TUBE	1	689446-2					
28	STRIPPER MOUNT BRACKET			69	LUBRICATOR ASS'Y	1	465104-2					
29	STRIPPER BUSHING			70	TERMINAL LUBRICATOR		2201431					
30	STOCK DRAG	1	375381	71								
31	STOCK DRAG HANDLE		375382	72								
32	STOCK DRAG STUD	2	354045-1	REV. REVISION RECORD								
33	STOCK DRAG SPRING 1-23847-1	2	30038	A1	INACTIVATED	4/1/62	W/L-6293					
34	STOCK DRAG ADJ. SCREW	2	372997	B	REACTIVATE 13, 14, 31, 33, 45, 47	4-26-71	W/L-0248					
35	FEED FINGER HOLDER			C	REV PER ECN	6-27-72	W/L-8955					
36	FEED FINGER	1	375093	D	REV PER ECN	3-26-73	W/L-9583					
37	FEED FINGER TIP			E	REV PER ECN	4-25-77	W/L-1969					
38	FEED FINGER SPACER			E1	INACTIVE FRO	12-15-75	W/L-19439					
39	BASE CASTING	1	570238	E2	OBSOLETE	5/11/77	W/L-19143					
40	GUARD 457664-2	1	473009	E3	INACTIVE-FRO	8/16/77	W/L-2161					
41				F	REV. PER ECN	4/80	W/L-193518					

☐ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON AMP-O-ELECTRIC 1-471273-3

MECH FEED		DIST.	4
Alignment Gage 67959T-1		DESIGNED	W. G. Horn
SERIAL NO.	DATE SHIPPED	CHK'D BY	W. G. Horn
CUSTOMER NAME AND ADDRESS		APPROVED	W. G. Horn
APPLICATOR NUMBER	REV. H	672076-2	SHEET 1 of 1