



- NOTES:**
- MATERIALS:  
 HOOD: PBT GF UL94 V-0 BLACK  
 FRONTSEALING: SILICONE VMQ BLUE  
 SCREW: STAINLESS STEEL  
 O-RING: NBR BLACK
  - TEMPERATURE RANGE: -30°C TO +90°C
  - RECOMMENDED TORQUE FOR SCREW:  
 35Ncm (3.1 in.LB)  
 MAX. TORQUE: 68Ncm (6 in.LB)
  - SINGLE PACKED

\* COMPLETELY TIGHTENED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale:	1,5:1 (1:1)	
	±0,3 unless otherw. specified				material:	SEE NOTES	
	date	name		title:			
	drawn 07.02.2014	Heinrich		WATER RESISTANT D-SUB HOOD			
	appd. 07.02.2014	Huether		50 POS.			
	norm			SHORT SCREW 4-40UNC STAINLESS STEEL			
	d-old			dwg no:			
	a	Origin			15K1A1439		DIN-A3
	rev.	description	date	name	part no:		sh: 1
					15-004750		

