

SPECIFICATION SHEET

55A4841

CABLE, ELECTRIC, RADIATION-CROSSLINKED, EXTRUDED, MODIFIED, FLUOROPOLYMER-INSULATED,
FOUR CONDUCTOR, JACKETED, NORMAL WEIGHT

20 December 1982


150°C

Revision A

The complete requirements for procuring the cable described herein shall consist of this document and the issue in effect of Raychem Specification 55A.

COMPONENT WIRES - 55A0811

JACKET - RADIATION-CROSSLINKED,
EXTRUDED, MODIFIED
FLUOROPOLYMER



CABLE CONSTRUCTION DETAILS						
PART NUMBER	CONDUCTOR SIZE (AWG)	JACKET THICKNESSES (in.)		OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lbs/1000 ft)
		MINIMUM	NOMINAL 1/	NOMINAL 1/	MAXIMUM	
55A4841-26-#	26	.006	.0075	.112	.131	9.3
55A4841-24-#	24	.006	.0075	.124	.144	12.0
55A4841-22-#	22	.006	.0075	.138	.164	16.4
55A4841-20-#	20	.006	.0075	.158	.186	23.3
55A4841-18-#	18	.006	.0075	.184	.216	34.1
55A4841-16-#	16	.006	.0075	.204	.241	42.3
55A4841-14-#	14	.007	.0085	.247	.289	63.1
55A4841-12-#	12	.007	.0085	.288	.336	92.6
55A4841-10-#	10	.008	.0095	.348	.410	143.

1/ Nominal values are for information only. Nominal values are not requirements.

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)

ACCELERATED AGING: 300 ± 3°C for 7 hours

BLOCKING: 200 ± 3°C for 6 hours

DIELECTRIC WITHSTAND: 1500 volts, 60 Hz

FLAMMABILITY:

Procedure 1, 3 seconds (maximum); 3 in. (maximum);
no flaming of facial tissue

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)

Tensile Strength, 5000 psi (minimum)

LIFE CYCLE: 200 ± 3°C for 168 hours

LOW TEMPERATURE-COLD BEND: -65 ± 2°C

THERMAL SHOCK: 290 ± 3°C for 4 hours

VOLTAGE WITHSTAND TEST: (After Accelerated Aging,
Immersion, Life Cycle, and Low Temperature-Cold Bend)
1000 volts, 60 Hz, 1 minute

PART NUMBER:

The "##" in the part numbers above shall be replaced by color code designators in accordance with MIL-STD-681 with a slash separating component wire colors and a dash separating the component wire colors from the jacket color.

Example: AWG 20, white, black, red and blue component wires; white jacket: 55A4841-20-9/0/2/6-9.

Raychem

Raychem Corporation
300 Constitution Drive, Menlo Park, California 94025
4151 361 3333 TWX 910 373 1205

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.