

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1)</sup>	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C <sup>(2)</sup>
	OPERATING HUMIDITY RANGE	40 % TO 80 %	STORAGE HUMIDITY RANGE	40 % TO 70 % <sup>(2)</sup>
	VOLTAGE	200 V AC	APPLICABLE CABLE	AWG #26 TO #36
	CURRENT	2 A	INSULATION	—

**SPECIFICATIONS**

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING	CONFIRMED VISUALLY.		×	×
<b>ELECTRIC CHARACTERISTICS</b>				
INSULATION RESISTANCE	500 V DC	1000 MΩ MIN.	×	—
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	×	—
<b>ENVIRONMENTAL CHARACTERISTICS</b>				
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.	1) INSULATION RESISTANCE: 1000 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +15 TO +35 → +85 → +15 TO +35 °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				

REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. (2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. Unless otherwise specified, refer to MIL-STD-1344.	APPROVED	HS. OKAWA	15.06.08
	CHECKED	HT. YAMAGUCHI	15.06.08
	DESIGNED	MT. ITANO	15.06.08
	DRAWN	MT. ITANO	15.06.08

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC-083001-00-00
--	-------------	------------------

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	A4B-16S-2C	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL622-0310-4-00	△ 1/1