

## Specification Sheet

Part Number: 170-03162



Nomex® High Temperature Woven Sleeveing, .75" Dia, GN, 100 ft/bulk reel

<b>Article Number</b>	170-03162
<b>Type</b>	BSNMX345B
<b>Color</b>	Green (GN)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Self extinguishing material does not melt and is unaffected by most acids, and provides excellent thermal stability against direct flame.</li><li>• Meets FMVSS 302 specifications for use in automotive engineering.</li><li>• Material cuts with ordinary scissors which reduces assembly time.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	A densely woven aramid fiber sleeveing, this soft and flexible material is self extinguishing and can withstand temperatures reaching up to 662°F.
<b>Short Description</b>	Nomex® High Temperature Woven Sleeveing, .75" Dia, GN, 100 ft/bulk reel

Global Part Name

BSNMX345B-NOMEX®-GN

Length L (Imperial)

100.0

Length L (Metric)

30.48

Bundle Diameter Min (Imperial)

0.56

Bundle Diameter Min (Metric)

14.2

Bundle Diameter Max (Imperial)

1.0

Bundle Diameter Max (Metric)

25.4

Diameter D (imperial)

0.75

Diameter D (metric)

19.1

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.1

Material

Polyaramid Polymetaphenylene Isophthalamide

Material Shortcut

NOMEX®

Flammability

UL VW-1

Halogen free

Yes

<b>Operating Temperature (Metric)</b>	-320°F to +650°F (-196 °C to +350 °C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909987
<b>Weight (Metric)</b>	0.61
<b>Weight (Imperial)</b>	1.34