



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	REVISED	10/17/86	[Signature]

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50 ±1</u>	Interface Dimensions MIL-STD-348A, Fig. 310-1	Temperature Rating <u>-55°C TO +125°C</u>
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D.
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>	Torque <u>7-10 IN-LBS</u>	Shock MIL-STD-202, Method 213, Condition B.
VSWR <u>1.05 ±.005 f(GHz)</u>	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B.
Insertion Loss (dB MAX) <u>0.06 √f(GHz)</u>	Insertion (MAX Lbs) <u>N/A</u>	Moisture Resistance MIL-STD-202, Method 106, Except Vibration
RF Leakage (dB MIN) <u>-70 f(GHz)</u>	Withdrawal (MIN Oz) <u>N/A</u>	Shall Be Omitted.
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u>	Center Contact Captivation	
Contact Resistance (Milliohms MAX)	Axial (Lbs) <u>6.0</u>	
Center Contact <u>3.0</u>	Radial (In-Oz) <u>4.0</u>	
Outer Contact <u>2.0</u>	Cable Retention	
Cable to Housing <u>N/A</u>	Axial Force (Lbs) <u>N/A</u>	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>	Torque (In-Oz) <u>N/A</u>	
IR.(Megohms MIN) <u>5,000</u>	Weight (Grams) <u>TBD</u>	

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY <u>JB</u> DATE <u>7/28/87</u>	
FRAC. ± 1/64	CHECKED BY <u>MH/M</u> DATE <u>8/6/87</u>	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
DEC. ±.005	APPD BY <u>BAR</u> DATE <u>8/6/87</u>	
ANGLES ± 1°	TITLE <u>OSM STRAIGHT PANEL PLUG 4 HOLE FLANGE MOUNT RECEPTACLE TAB TERMINAL</u>	
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	NO. A.P. <u>N/A</u>
	SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>
	SCALE <u>5:1</u>	2051-5339-02
		REV <u>01₁</u>
		SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1060124-1
SHEET 1 OF 1 REV A