

# AMGP-6432

## 28-31 GHz 2W SMT Packaged Power Amplifier



### Data Sheet




#### Description

The AMGP-6432 is a surface mount packaged 2-Watt power amplifier that operates from frequencies between 28 to 31 GHz. In the operational frequency band from 29.25 to 30 GHz, it provides 33 dBm of typical output power ( $P_{1dB}$ )/ 34 dBm  $P_{sat}$  and 21.5dB of small-signal gain. This PA is also suitable for high linear application where the PA demonstrates greater than -38dBc of third order output inter modulation (OIM3) at +18dBm/ tone output power level.

#### Features

- 5 x 5 mm surface mount package
- > +33 dBm Output Power from 28.5 to 31 GHz
- 50  $\Omega$  input and output match
- -40° C to +85° C operation

#### Functional Block Diagram




Pin	Function
1	Vg
2	Vd1
3	Vd2
4	RF_OUT
5	Vd2
6	Vd1
7	Vg
8	RF_IN

#### Applications


- VSAT
- Microwave Radio System
- Satellite Up/Down Link

Note: This part is not rated for high-moisture environments.



**Attention: Observe Precautions for handling electrostatic sensitive devices.**  
 ESD Machine Model (Class A): 60 V  
 ESD Human Body Model (Class 1A): 200 V  
 Refer to Avago Application Note A004R: Electrostatic Discharge Damage and Control.

#### Package Diagram



## ELECTRICAL SPECIFICATIONS

**Table 1. Absolute Minimum and Maximum [1] Ratings**

Parameter	Specifications			Comments	
Description	Pin	Min.	Max.	Unit	
Drain Supply Voltage	V <sub>d1</sub> V <sub>d2</sub>		6.5	V	
Gate Supply Voltage	V <sub>g</sub>	-2	0	V	
RF Input Power (P <sub>in</sub> ) [2]	RFIN		24	dBm	CW
Power Dissipation (P <sub>diss</sub> )			10	W	P <sub>diss</sub> = V <sub>d1</sub> × I <sub>d1</sub> + V <sub>d2</sub> × I <sub>d2</sub> + P <sub>in</sub> - P <sub>out</sub>
MSL			MSL2		
T <sub>CH</sub>			150	°C	Channel Temperature
T <sub>STG</sub>		-65	150	°C	Storage Temperature

Notes:

1. Operation of this device above any one of these maximum parameters may cause permanent damage
2. With the DC (typical bias) and RF applied to the device at board temperature T<sub>b</sub> = 25° C

**Table 2. Recommended Operating Range**

Parameter	Specifications					Comments
Description	Pin	Min.	Typical	Max.	Unit	
Drain Supply Voltage	V <sub>d1</sub> V <sub>d2</sub>		6.0		V	
Gate Supply Voltage	V <sub>g</sub>	-1	-0.68	-0.6	V	
Maximum Gate Current	I <sub>g, max</sub>	-3	-2.5		mA	I <sub>g, max</sub> occurs at highest RF P <sub>out</sub> condition.
Quiescent Drain Supply Current (I <sub>dq</sub> )	V <sub>d1</sub> V <sub>d2</sub>		300 400		mA	I <sub>dq</sub> = I <sub>d1</sub> + I <sub>d2</sub>
RF Output Power (P <sub>out</sub> )	RFOUT		33		dBm	CW
Frequency Range		28		31	GHz	
Thermal Resistance, θ <sub>ch-b</sub>			7.6		°C/W	Channel to board
Base Plate Temperature		-40		+85	°C	

## Electrical Specifications

All data measured on a 2.4 mm connectorized production contactor board (Rogers 4350B) at  $V_{dd1} = V_{dd2} = 6\text{ V}$ ,  $I_{dq} = 0.7\text{ A}$  ( $I_{dq1} + I_{dq2}$ ),  $T_c = 25\text{ }^\circ\text{C}$ , and  $50\text{ }\Omega$  at all ports, unless otherwise stated.


**Table 3. RF Electrical Characteristics**

Parameter	Performance			Unit	Comments
	Min.	Typical	Max.		
Frequency Range (GHz)	28		31	GHz	
Input Return Loss (dB)		-15		dB	Small Signal
Output Return Loss (dB)		-12		dB	Small Signal
Gain (dB) <sup>[1]</sup> @ Freq = 29.25 GHz	18	21.5	25	dB	$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
( $P_{in} = 0\text{ dBm}$ ) @ Freq = 30 GHz	18	21.3	25		$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
Reverse Isolation (dB)		-50		dB	Small Signal
$P_{out}$ <sup>[1]</sup> @ Freq = 29.25 GHz	33	34.8		dBm	$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
( $P_{in} = 17\text{ dBm}$ ) @ Freq = 30 GHz	33	34.3			$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
$P_{1dB}$ @ Freq = 29.25 GHz		33.9			$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
@ Freq = 30 GHz		32.9			$V_{dd} = 6\text{ V}$ , $I_{dq} = 0.7\text{ A}$
IM3 Level		-38		dBc	$\Delta f = 20\text{ MHz}$ , $P_{out} = 20\text{ dBm/tone}$
Total Drain Current		0.7		A	$I_{dq}$


Note:

1.  $P_{out}$  and Gain measurement accuracy is subjected to the tolerance of  $\pm 0.5\text{ dBm}$ , respectively.


**Product Consistency Distribution Charts at 29.25 GHz and 30 GHz,  $V_{dd} = 6\text{ V}$ ,  $I_{dq} = 0.7\text{ A}$**




$V_g$  @  $V_{dd} = 6\text{ V}$ ,  $I_{dq} = 0.7\text{ A}$ , Mean =  $-0.68\text{ V}$ , LSL =  $-1\text{ V}$ , USL =  $-0.6\text{ V}$




$P_{out}$  @ 29.25 GHz ( $P_{in} = 17\text{ dBm}$ ), Mean =  $34.8\text{ dBm}$ , LSL =  $33\text{ dBm}$



$P_{out}$  @ 30 GHz ( $P_{in} = 17\text{ dBm}$ ), Mean =  $34.3\text{ dBm}$ , LSL =  $33\text{ dBm}$



Gain @ 29.25 GHz, Mean =  $21.5\text{ dB}$ , LSL =  $18\text{ dB}$ , USL =  $25\text{ dB}$



Gain @ 30 GHz, Mean =  $21.2\text{ dB}$ , LSL =  $18\text{ dB}$ , USL =  $25\text{ dB}$

## Selected Performance Plots

All data measured on a 2.4 mm connector based evaluation board at  $V_{dd1} = V_{dd2} = 6\text{ V}$ ,  $I_{dq} = 0.7\text{ A}$  ( $I_{d1} + I_{d2}$ ),  $T_A = 25^\circ\text{ C}$ , and  $50\ \Omega$  at all ports.




Figure 1. S<sub>21</sub> (dB) Frequency Sweep




Figure 2. S<sub>11</sub> (dB) Frequency Sweep




Figure 3. S<sub>22</sub> (dB) Frequency Sweep




Figure 4. S<sub>12</sub> (dB) Frequency Sweep




Figure 5. P<sub>1dB</sub> (dBm) Frequency Sweep




Figure 6. IM3 level (dBc) vs. Output power/tone

## Selected Performance Plots over Operating Temperature Range

All data measured on a 2.4 mm connector based evaluation board at  $V_{dd1} = V_{dd2} = 6\text{ V}$ ,  $I_{dq} = 0.7\text{ A}$  ( $I_{d1} + I_{d2}$ ), and  $50\ \Omega$  at all ports.  $I_{dq}$  has been maintained at  $0.7\text{ A}$  under different temperature conditions. Plotted data shown this page includes evaluation board loss and connector loss approximately  $0.5\text{ dB/one side}$ .




Figure 7.  $S_{21}$  (dB) Frequency Sweep over Temperature




Figure 8.  $S_{11}$  (dB) Frequency Sweep over Temperature




Figure 9.  $S_{22}$  (dB) Frequency Sweep over Temperature




Figure 10. Typical  $V_{gs}$  for  $I_{dq} = 0.7\text{ A}$  over Temperature




Figure 11.  $P_{1dB}$  (dBm) Frequency Sweep over Temperature




Figure 12. OIP3 (dBm) and IM3 level (dBm) Frequency Sweep over Temperature @  $P_o = 20\text{ dBm/tone}$

## Selected Performance Plots Over Operating Supply Voltage Range

All data measured on a 2.4 mm connector based evaluation board at  $T_A = 25^\circ\text{C}$ , and  $50\ \Omega$  at all ports. Plotted data shown this page includes evaluation board loss and connector loss approximately 0.5 dB/one side.




Figure 13.  $S_{21}$  (dB) Frequency Sweep




Figure 14.  $S_{11}$  (dB) Frequency Sweep




Figure 15.  $S_{22}$  (dB) Frequency Sweep




Figure 16.  $P_{1dB}$  (dBm) Frequency Sweep




Figure 17.  $P_{3dB}$  (dBm) Frequency Sweep




Figure 18. OIP3 and IM3 level vs. Frequency Sweep @  $P_o = 20\ \text{dVm/tone}$

## Application Circuit




Figure 19. Application Circuit

Table 3. Typical Test Conditions:

PIN		
Vd1, 2	6V	Drain Supply Voltage
Idsq=Id1+Id2	700mA	Quiescent Drain Current
Vg	-0.83	Gate Supply Voltage

Table 4. Pin Description

Pin No.	Function
1	Vg
2	Vd1
3	Vd2
4	RF_OUT
5	Vd2
6	Vd1
7	Vg
8	RF_IN

## Demo-board




Figure 20. Demo-board

Table 5. Recommended Passive Components

Ref Designator	Value	Part Number
C1-C4	22uF	TDK C1608X5R0J226M DigiKey 445-8028-1-ND
C5-C10	0.1uF	0402 ANY
L1, L2	Ferrite Bead	Murata BLM18HG471SN1
R1-R6	10Ω	0402 ANY
R7, R8	47	0402 ANY

## Bias Sequence:

- Apply Vg [Pin 1 or Pin 7] = -1.5V
- Apply Vdd [Pin 3 and Pin 5] = 0V
- Increase Vdd to 6V
- Increase Vg obtain Idsq = 0.7A
- Apply RF Input
- Turn off in reverse order



## Reliability Data

Please contact Avago Technical and/or Customer supports for more detail [www.avagotech.com](http://www.avagotech.com)

## Package Dimension, PCB Layout and Tape and Reel information

Please refer to Avago Technologies Application Note 5521, AMxP-xxxx production Assembly Process (Land Pattern B).

### Part Number Ordering Information

Part Number	Devices per Container	Container
AMGP-6432-BLKG	10	antistatic bag
AMGP-6432-TR1G	100	7" Reel
AMGP-6432-TR2G	500	7" Reel

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries.  
Data subject to change. Copyright © 2005-2013 Avago Technologies. All rights reserved.  
AV02-3203EN - August 27, 2013

