



▲ HARDWARE SUPPLIED ON SWITCH

NOTES:

1. ALL DIMENSION IN MM [INCH]
2. GENERAL TOLERANCE: X: X=±0.4 X:XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC 350mA, 110V AC/DC
5. CONTACT RATING (NON-SWITCHING) 5A
6. CONTACT MATERIAL: SILVER over COPPER ALLOY.
7. OPERATING FORCE: 42±100 CM/STANDARD
8. OPERATING TEMP: -30° to 85°C
9. CIRCUIT SP: 5 POSITIONS, 30° INDEX.
10. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
11. ▲ DENOTES CRITICAL PARAMETER.
12. HARDWARE SUPPLIED ON SWITCH - SEE BELOW STOPRING, LOCKWASHER, & HEXNUT

A	13306	RELEASED FOR PRODUCTION	7/21/03	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE				
KC15A9.501SLS				
SCALE	DATE	DR	DWG	REV
1.5:1	7/21/03	AR	G527543	A

E-SWITCH®

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED