


## Photovoltaic Solarcell Protection Schottky Rectifier

High Barrier Technology for Improved High Temperature Performance

This datasheet reflects specifications of product in actual application.



P600

### FEATURES

- Guardring for overvoltage protection
- Low forward voltage drop, low power losses
- High efficiency operation
- High forward surge capability
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

For use in solar cell junction box as a bypass diode for protection, using DC forward current without reverse bias.

### MECHANICAL DATA

**Case:** P600, molded epoxy over passivated junction  
Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** Color band denotes cathode end

PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	15 A
$V_{RRM}$	45 V
$I_{FSM}$	300 A
$V_F$ at $I_F = 15$ A	0.46 V
$T_{OP}$ max.	175 °C

MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)			
PARAMETER	SYMBOL	SB15H45	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	45	V
Maximum average forward rectified current (fig. 1)	$I_{F(AV)}^{(1)}$	15	A
	$I_{F(AV)}^{(2)}$	7	
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	300	A
Operating junction and storage temperature range	$T_{OP}, T_{STG}$	- 55 to + 175	°C
Junction temperature in DC forward current without reverse bias, $t \leq 1$ h (fig. 1)	$T_J^{(3)}$	$\leq 200$	°C

#### Notes

(1) With heatsink,  $T_L = 25$  °C

(2) Without heatsink, free air

(3) Meets the requirements of IEC 61215 ed. 2 bypass diode thermal test

ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted)						
PARAMETER	TEST CONDITIONS		SYMBOL	TYP.	MAX.	UNIT
Instantaneous forward voltage	I <sub>F</sub> = 5 A	T <sub>A</sub> = 25 °C	V <sub>F</sub> <sup>(1)</sup>	0.48	-	V
	I <sub>F</sub> = 7.5 A			0.50	-	
	I <sub>F</sub> = 15 A			0.56	0.64	
	I <sub>F</sub> = 5 A	T <sub>A</sub> = 125 °C		0.35	-	
	I <sub>F</sub> = 7.5 A			0.39	-	
	I <sub>F</sub> = 15 A			0.46	0.54	
Reverse current	V <sub>R</sub> = 45 V	T <sub>A</sub> = 25 °C	I <sub>R</sub> <sup>(2)</sup>	10	300	μA
		T <sub>A</sub> = 125 °C		8	20	mA
Typical junction capacitance	4.0 V, 1 MHz		C <sub>J</sub>	1020	-	pF

Notes

- (1) Pulse test: 300 μs pulse width, 1 % duty cycle
- (2) Pulse test: 10 ms pulse width

THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	SB15H45	UNIT
Thermal resistance	R <sub>θJA</sub> <sup>(1)</sup>	66	°C/W
	R <sub>θJL</sub> <sup>(1)</sup>	14	
Typical thermal resistance	R <sub>θJL</sub> <sup>(2)</sup>	3.5	°C/W

Notes

- (1) Without heatsink, free air
- (2) T<sub>A</sub> = 75 °C, T<sub>L</sub> = 125 °C, T<sub>J</sub> = 175 °C, infinite mass at 0.375" (9.5 mm) lead length

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
SB15H45-E3/54	1.756	54	800	13" diameter paper tape and reel

RATINGS AND CHARACTERISTICS CURVES

(T<sub>A</sub> = 25 °C unless otherwise noted)




Fig. 1 - Forward Current Derating Curve

Notes

- Mounted on junction box
- Using DC forward current
- Junction box SA (sink to ambient)
- Assumes R<sub>θLS</sub> (lead to sink) of 5 °C/W
- Thermal resistance R<sub>θSA</sub> (sink to ambient):

$$R_{\theta SA} = \frac{(T_J - T_A)}{P_D} - (R_{\theta JL} + R_{\theta LS})$$

P<sub>D</sub>: Power dissipation P<sub>D</sub> = V<sub>F</sub> x I<sub>F</sub>




Fig. 2 - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Junction Capacitance





Fig. 3 - Typical Reverse Characteristics

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.