



**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING : 150 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

**MECHANICAL:**

1. HOUSING MATERIAL : NYLON UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE  $\phi 0.46\text{mm}$ .
3. PLATING : GOLD PLATING OVER NICKEL.
4. OPERATING LIFE : 750 CYCLES MIN.
5. PCB RETENTION PRE-SOLDER : 1 LB MIN.
6. PCB RETENTION POST-SOLDER: 10 LBS MIN.

**ENVIRONMENTAL:**

1. STORAGE TEMPERATURE :  $-40^{\circ}\text{C}$  TO  $+85^{\circ}\text{C}$ .
2. OPERATION TEMPERATURE:  $-40^{\circ}\text{C}$  TO  $+85^{\circ}\text{C}$ .
3. WAVE SOLDERING TEMPERATURE:  $255\sim 265^{\circ}\text{C}$  (5~10 SECONDS)
4. RoHS COMPLIANT.

MATES WITH MODULAR PLUG CONFORMING TO

PART NUMBER	CONTACT	COLOR	GOLD PLATING
E5362-S00512-L	2	BLACK	6u"
E5364-S00312-L	4	GRAY	6u"
E5364-S00313-L	4	GRAY	15u"
E5364-S00512-L	4	BLACK	6u"
E5366-S00312-L	6	GRAY	6u"

DETACHED LISTS	MM (INCH)	<b>RoHS Compliant</b>	<b>Pulse</b> A TECHNITROL COMPANY	
	TOLERANCES EXCEPT AS NOTED	TITLE 11.5 SIDE ENTRY 6P		
	MM		DFTO Cathy	DRAWING NO. CE533A31-LA
	.0 ± 0.2	±	DATE 08/21/2006	/PART NO. SEE TABLE
	.00 ± 0.15	±	DO NOT SCALE DRAWING	
	.000 ± 0.075	±	SHEET 1 OF 1	
	ANGLES ± 0.5		SCALE : 3:1	SIZE REV A3 0
	THIRD ANGLE PROJECTION			