



ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Iex	@ 115V, 400Hz, PIN 1 - PIN 2	140mA Max.
Sec. N.L.V	@ 115V, 400Hz, PIN 1 - PIN 2	
	PIN 3 - PIN 4 =	13.74V ±2%
	PIN 5 - PIN 6 =	13.74V ±2%
DCR	@ 20°C, PIN 1 - PIN 2 =	7.800 Ω ±20%
	@ 20°C, PIN 3 - PIN 4 =	0.236 Ω ±20%
	@ 20°C, PIN 5 - PIN 6 =	0.236 Ω ±20%
HIPOT	PRIMARY - SECONDARY	1500V, 60Hz, 1 SEC

REV.#	REVISION	DATE	HAMMOND ELECTRONIC DIVISION		52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5	PH # (519) 886-6181 FAX # (519) 886-9540
0	RELEASED.	07/10/15	MANUFACTURING™			
			DWG. BY: C. ILIE	CHK'D BY:	TITLE: POWER TRANSFORMER	DWG. NO. 227P
			DATE: 07/10/15	APP'D. BY:		
				DIMENSIONS: IN(X) MM()		