

Contact insert - VC-TFS 5/1M-PEA - 1607502

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Contact insert with integrated sleeve frame, 1 free module slot, type VC 4, 4-pos. + PE, 690 V / 70 A



Product Features

- Compact design
- Universal connection
- Proven COMBICON technology
- Can be keyed to prevent incorrect connection

Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 969165
Weight per Piece (excluding packing)	61.56 GRM
Custom tariff number	85366990
Country of origin	Poland

Technical data

General

Note	Connectors may only be connected/disconnected when under no load.
Connection method	Screw connection
	Screw connection
Tightening torque	1.2 Nm ... 1.8 Nm
Pollution degree	3
Surge voltage category	III
Number of positions	4+PE
Insertion/withdrawal cycles	≥ 50
Design	VC4
Conductor cross section AWG/kcmil min.	20

Contact insert - VC-TFS 5/1M-PEA - 1607502

Technical data

General

Conductor cross section AWG/kcmil max	6
2 conductors with same cross section, solid min.	0.5 mm ²
2 conductors with same cross section, solid max.	6 mm ²
2 conductors with same cross section, stranded min.	0.5 mm ²
2 conductors with same cross section, stranded max.	4 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	4 mm ²
Conductor cross section	0.5 mm ² ... 16 mm ²
Connection cross section AWG	20 ... 6
Stripping length of the individual wire	14 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

Material data

Inflammability class according to UL 94	V0
Contact material	CuZn
Contact surface material	hard-silver plated
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	690 V
Rated surge voltage	6 kV
	6 kV
Rated current	70 A
	70 A

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

Contact insert - VC-TFS 5/1M-PEA - 1607502

Classifications

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals


Approvals submitted

Approval details


UL Recognized 	
mm ² /AWG/kcmil	20-6
Nominal current I _N	55 A
Nominal voltage U _N	600 V

Contact insert - VC-TFS 5/1M-PEA - 1607502

Approvals

cUL Recognized 	
mm ² /AWG/kcmil	20-6
Nominal current I _N	45 A
Nominal voltage U _N	600 V

GOST 	
--	--

cULus Recognized 	
--	--