



Left Side
 Connector(s): LC-Duplex Secure
 Mode: MM
 Housing Color: Rose
 Geom. Spec: N/A

Fiber Path
 A - _____ - B
 B - _____ - A

Right Side
 Connector(s): LC-Duplex
 Mode: MM
 Housing Color: Beige
 Geom. Spec: N/A

- Notes:
- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
 - 2 Includes dust caps (not shown on print).
 - 3 IL tested at 1300nm.
 - 4 Label 2 will not be present on any cable assembly less than 5 meters long.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS TO BE USED ONLY BY THE PERSONNEL TO WHOM IT IS ISSUED. IT MAY NOT BE DISCLOSED TO ANYONE OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

A	Rev Per EC#	RELEASE	5/15/2007	-	DF			
P	LTR	REVISION RECORD	DATE	DN	APVD			

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	0 PLC ± .
	1 PLC ± .
	2 PLC ± .
	3 PLC ± .
	4 PLC ± .

Restricted To:

DWG	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Dave Fennell		
APVD	Dave Fennell	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex		
SCALE	SIZE	DRAWING NO	SHEET
NTS	A2	C- 1906017	1 of 4
			REV
			A

THIS DRAWING IS A CONTROLLED DOCUMENT.

Part #	L (meters)	L (feet)	LC-Duplex Secure, Rose		LC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1906017-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	-
0-1906017-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	-
0-1906017-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	-
0-1906017-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	-
0-1906017-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	-
0-1906017-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	-
0-1906017-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	-
0-1906017-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	-
0-1906017-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	-
1-1906017-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	-
1-1906017-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	-
1-1906017-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	-
1-1906017-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	-
1-1906017-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	-
1-1906017-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	-
1-1906017-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	-
1-1906017-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	-
1-1906017-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	-
1-1906017-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	-
2-1906017-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	-
2-1906017-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	-
2-1906017-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	-
2-1906017-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	-
2-1906017-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	-
2-1906017-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	-
2-1906017-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	-
2-1906017-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	-
2-1906017-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	-
2-1906017-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	-
3-1906017-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	-
3-1906017-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	-
3-1906017-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	-
3-1906017-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	-
3-1906017-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	-
3-1906017-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	-
3-1906017-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	-
3-1906017-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	-
3-1906017-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	-
3-1906017-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	-
4-1906017-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	-
4-1906017-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	-
4-1906017-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	-

Qty	U of M	Description	Item No.
2	piece	Trace Label	7
4	piece	Eyelet/Shrink tube assembly - White	6
AR	meter	2 fiber, 50/125, 2.0mm, Twinzip, Orange, OFNR (Riser)	5
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	4
2	piece	LC Connector Assy, MM	3
2	piece	LC Duplex clip, black	2
4	piece	LC, SC, FC Straight Boot, Beige	1

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
 CE
 DIST
 16

A	Rev Per	EC#	RELEASE	5/15/2007	-	DF				
P	LTR		REVISION RECORD	DATE	DIN	APVD				

DIMENSIONS: meters
 TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 P.L.C ± -
 1 P.L.C ± -
 2 P.L.C ± -
 3 P.L.C ± -
 4 P.L.C ± -

DIN	Cable Assy Configurator		MATERIAL	HEAT TREAT
OK	Dave Fennell			
APVD	Dave Fennell		Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex			
SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1906017	2 of 4	A

Restricted To:

THIS DRAWING IS A CONTROLLED DOCUMENT. DFC#0

USED ON

Part #	L (meters)	L (feet)	LC-Duplex Secure, Rose		LC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1906017-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	-
4-1906017-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	-
4-1906017-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	-
4-1906017-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	-
4-1906017-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	-
4-1906017-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	-
4-1906017-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	-
5-1906017-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	-
5-1906017-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	-
5-1906017-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	-
5-1906017-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	-
5-1906017-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	-
5-1906017-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	-
5-1906017-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	-
5-1906017-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	-
5-1906017-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	-
5-1906017-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	-
6-1906017-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	-
6-1906017-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	-
6-1906017-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	-
6-1906017-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	-
6-1906017-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	-
6-1906017-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	-
6-1906017-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	-
6-1906017-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	-
6-1906017-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	-
6-1906017-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	-
7-1906017-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	-
7-1906017-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	-
7-1906017-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	-
7-1906017-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	-
7-1906017-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	-
7-1906017-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	-
7-1906017-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	-
7-1906017-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	-
7-1906017-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	-
7-1906017-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	-
8-1906017-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	-

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS, INC. ANY UNAUTHORIZED DISCLOSURE OR REPRODUCTION OF THIS INFORMATION IS STRICTLY PROHIBITED. CONTACT TYCO ELECTRONICS PERSONNEL FOR ANY INFORMATION ON THIS DOCUMENT. THIS DRAWING IS A CONTROLLED DOCUMENT. HARRISBURG, PENNSYLVANIA

LOC
CE
DIST
16

A	Rev Per	EC#	RELEASE	5/15/2007	-	DF	
P	LTR		REVISION RECORD	DATE	DIN	APVD	

DIMENSIONS: meters

 TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ±
 1 PLC ±
 2 PLC ±
 3 PLC ±
 4 PLC ±
Restricted To:

DIN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
CHK	Dave Fennell	Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD	Dave Fennell	NAME: FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex			
SCALE	NTS	SIZE	A2	DRAWING NO	C- 1906017
SHEET	3 of 4	REV	A		

8 7 6 5 4 3 2 1

A
B
C
D

Label 1

Per specification 107-1645-1



- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1



- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ORGANIZATION WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

A	Rev Per EC#	RELEASE	5/15/2007	-	DF				
P	LTR	REVISION RECORD	DATE	DIN	APVD				

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
meters			
0 PLC	± .		
1 PLC	± .		
2 PLC	± .		
3 PLC	± .		
4 PLC	± .		

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT	
CHK	Dave Fennell			
APVD	Dave Fennell	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608		
NAME	FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex			
SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1906017	4 of 4	A

D
C
B
A