


Minimum cable diameter:  $\varnothing F_{max} = 3$

- Maximum cable diameter:
- with rubber bushing:  $\varnothing F_{max} = 6,5$
  - without rubber bushing:  $\varnothing F_{max} = 8,5$
  - without reduction plate:  $\varnothing F_{max} = 12,5$

|                    |                |
|--------------------|----------------|
| <b>09670150334</b> | <b>4-40UNC</b> |
| Part number        | screw thread   |

|   |  |  |                        |                        |                 |  |
|---|--|--|------------------------|------------------------|-----------------|--|
|  | All rights reserved<br>Department EC PD - FR | All Dimensions in mm<br>Original Size DIN A4 |                        | Scale 1:1              | Free size tol.  | Ref.   |
|   |  | Created by DOUGE                             | Inspected by BAGDIKIAN | Standardisation KOHLER | Date 2013-01-29 | State Final Release                                      |
| HARTING Electronics GmbH<br>D-32339 Espelkamp                                       |  | Title D-Sub Hood 15P side entry full metal   |                        |                        |                 | Doc-Key / ECM-Nr.<br>100521709/UGD/001/A<br>500000056836 |
|   |  | Type TB                                      | Number 09670150334     |                        | Rev. A          | Page 1/1   |