

Specification Sheet

Part Number: 156-00457



Heavy-Duty Fir Tree Mount Cable Tie, 8" x .18", .03"-.28", Panel Thickness, PA46, Brown, 500/pkg

Article Number	156-00457
Type	T50RFT7HD
Color	Brown (BN)
Features & Benefits	<ul style="list-style-type: none">• Staggered fir tree branch design provides low insertion forces and high extraction forces.• Initial fir tree serves as a locating feature for assistance in blind assembly applications.• Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag

Product Description

Heavy Duty fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie, and is ideal in heavy duty environments.

Short Description	Heavy-Duty Fir Tree Mount Cable Tie, 8" x .18", .03"-.28", Panel Thickness, PA46, Brown, 500/pkg
Global Part Name	T50RFT7HD-PA46-BN
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	200.0
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	1.8
Bundle Diameter Max (Metric)	45.0

Height H (Imperial)	.78
Height H (Metric)	19.80
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.276
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.2 - 7.2 mm
Mounting Hole Diameter D Min (Imperial)	0.244
Mounting Hole Diameter D Max (Imperial)	0.284
Mounting Hole Diameter D Max (Metric)	7.2
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.9
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Material Cable Tie	Polyamide 4.6 (PA46)

Flammability UL 94 V2

Operating Temperature (Metric) +275°F (+135°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909987

Content Unit(BMEcat) pcs.