

## Specification Sheet

Part Number: T50L0UVC2



UV Resistant Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number	112-05460
Type	T50L
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Engineered and manufactured for maximum performance and quality.</li><li>• Made from 100% high-quality plastic to ensure efficient recycling.</li><li>• Inside serration for a strong hold onto bundles.</li><li>• Easy application either manually or with a tensioning tool.</li><li>• Bent tail allows for simpler insertion.</li></ul>
Quantity Per	bag

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	UV Resistant Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66UV, Black, 100/pkg
<b>Global Part Name</b>	T50L-PA66UV-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	15.35
<b>Length L (Metric)</b>	390.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.8
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	4.3
<b>Bundle Diameter Max (Metric)</b>	109.2

<b>Thickness T (Imperial)</b>	0.05
-------------------------------	------

**Thickness T (Metric)** 1.2

<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
-----------------	-------------------------------------

**Material Shortcut** PA66UV

<b>US MIL SPEC</b>	SAE-AS33671
--------------------	-------------

MS3367-5-0

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

CAGE Code 53421 Bundesamt für Wehrtechnik | VG 95387 Part 4 Edition:  
2008-12 UL-ZODZ2.E64139 BACS38K

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

<b>Package Quantity(Imperial)</b>	100
-----------------------------------	-----

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 2.7