



P1	P2
1	8
2	7
3	6
4	5
5	4
6	3
7	2
8	1

Extended Length ("L2")	Typical Retracted Length ("L1")
300.0 Inches - 28.75 Inches	126.0 Inches
7,620.0MM-8,763.0MM	3,200.4MM

Materials:

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36" [.014MM] Thick Phosphor Bronze
- Connector: 50µ" of Selective Gold Contact Plating
 - Area, Gold flash over the remainde
 - Over 2.54µm [.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X4C): PP6331 ID 0.95-1.0
- Jacket: PVC NOUL 80P
- Package: Individual PE Bag

Electrical:

- Voltage rating: 30V (DC)

Unit: MM

SEC: A-A



Scale	1:1						Name	Item No.	
TOLERANCE							Drawn	11.18.11	
X.X	±0.40						Chappell		
X.XX	±0.25						Approved		
X.XXX	±0.15								
Angle	±3°								
ASSMANN W+S+W components								AT-C-26-8/8/B-25	
								Title	
								NON-UL 26 AWG (0.16/7)*8C, O.D.: 2.4*8.8MM, Standard Plug, 50µ" of contact plating, Black	
								Drawing No.	
								rev00	
								Replace	
								Sheet	
Modification				Date	Name				