




# Thermal Transfer Labels

Panduit is a global leader in reliable and innovative solutions for identification and safety. Products are engineered for a wide variety of industries and applications – including electrical, electronics, industrial, and network. Panduit offers a complete, leading-edge line of labeling software, high-performance label materials (all RoHS compliant), and printers that provide enhanced productivity, dependability, and value to all infrastructure labeling requirements.





## Cable/Wire Labels

Turn-Tell® Labels . . . . .	4
Self-Laminating Labels . . . . .	5 – 7
LabelCore™ Fiber Optic Cable Identification System . . . . .	7 – 8
Flag Labels . . . . .	8
Non-Laminated Vinyl Cloth Labels . . . . .	9
Non-Laminated Nylon Cloth Labels . . . . .	10

## Marker Plates

High-Temperature Flame-Retardant Marker Plates . . . . .	11
Halogen-Free Flame-Retardant Marker Plates . . . . .	11
Standard Marker Plates . . . . .	12

## Heat Shrink Labels

Military Grade – Single-Sided Labels . . . . .	13
Military Grade – Two-Sided Labels . . . . .	14
Halogen-Free – Two-Sided Labels . . . . .	15
Fluid-Resistant – Two-Sided Labels . . . . .	16

## Component Labels/Continuous Tapes

Raised Panel Labels . . . . .	17 – 20
Polyester Component Labels . . . . .	21
Super-Tack Polyester Component Labels . . . . .	22
Tedlar® Component Labels . . . . .	23
Tamper-Evident Polyester Component Labels . . . . .	23
Non-Adhesive Polyester Component Labels . . . . .	24
Vinyl Cloth Component Labels . . . . .	24
Polyimide Component Labels . . . . .	25
Paper Component Labels . . . . .	26
Continuous Tapes . . . . .	26 – 28

## Safety and Solar Labels

Super-Tack Polyester Arc Flash Labels . . . . .	29
Raised Panel Arc Flash Labels . . . . .	29
Super-Tack Arc Flash Continuous Tapes . . . . .	30
Super-Tack Polyester Facility Identification Labels . . . . .	30
Polyester Photoluminescent Tapes . . . . .	31
Raised Panel Solar Labels . . . . .	31
Over-Laminate Labels . . . . .	32
Super-Tack Polyester Solar Labels . . . . .	32
Reflective Continuous Tapes for Solar Applications . . . . .	32

## Software/Printers/Accessories

Software . . . . .	33
TDP43ME Printers, Accessories and Ribbons . . . . .	34
TDP43HE & TDP46HE Printers, Accessories & Ribbons . . . . .	35

Tedlar is a registered trademark of E.I. du Pont de Nemours and Company.

## Turn-Tell® Labels

**PATENTED**

- Allows labels to rotate for visibility from any angle, and allows repositioning on the wire/cable to align legends for improved aesthetics

- Ideal for use in high-density or space-constrained cable applications
- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.						
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm									
R050X075V1T	White	0.50	12.7	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000						
R050X125V1T				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG								
R050X150V1T				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/Cat. 5e FTP/ 10 – 6 AWG								
R100X075V1T	TIA Blue TIA Green TIA Gray TIA Red TIA Yellow White TIA Blue TIA Green TIA Gray TIA Red TIA Yellow	1.00	25.4	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500						
R100X125V1T				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG								
R100X150V1T				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/								
R100X150V2T																				
R100X150V3T																				
R100X150V4T																				
R100X150V7T																				
R100X150V8T																				
R100X225V1T				2.25	57.2	0.75	19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6 UTP/ Cat. 6A FTP/8-4 AWG								
R100X225V2T																				
R100X225V3T																				
R100X225V4T																				
R100X225V7T																				
R100X225V8T																				
R100X400V1T				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG								
R150X150V1T															1.50	38.1	0.50	12.7	0.22	5.6
R200X150V1T																				
R200X225V1T	2.00	50.8	0.75										19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8 – 4 AWG		
R200X400V1T				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG								

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Vinyl Self-Laminating Labels

- Includes a colored print-on area and clear overlamine to protect the legend for clear and durable identification
- Sized specifically for wire and cable applications
- Thin and conformable; preferred material for most general wire/cable labeling
- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15-01, File # MH14979



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.	
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
S050X075VA1Y	White	0.50	12.7	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.1	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000	
S050X075VATY*														2500	
S050X125VA1Y				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0			Cat. 3 UTP/ 12 - 10 AWG	5000
S050X125VATY*															
S050X150VA1Y		1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG	5000				
S050X150VATY*															
S050X250VATY*		2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 – 2 AWG	5000				
S075X075VATY*															
S075X100VATY*		0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	5				
S075X125VATY*															
S075X150VATY*	Cat. 3 UTP/ 12 - 10 AWG														
S075X150VATY*		Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG													
S100X075VA1Y	TIA Blue TIA Brown TIA Green TIA Gray TIA Orange TIA Purple		1.00	25.4	0.75	19.1	0.25	6.4	0.08	0.50	2.0	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500
S100X075VATY*		5000													
S100X125VA1Y		1.25			31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG			5000
S100X125VATY*															
S100X150VA1Y		1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 - 6 AWG	5000				
S100X150VATY															
S100X150VBTY		Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 - 6 AWG	4												
S100X150VCTY															
S100X150VDTY															
S100X150VETY															
S100X150VFTY															
S100X150VGTY															

Order number of labels required in multiples of Standard Package Quantity.

\*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Vinyl Self-Laminating Labels (continued)

Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.												
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm															
S100X150VHTY*	TIA Red	1.00	25.4	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	4	5000												
S100X150VITY*	TIA Yellow																									
S100X150V0TY*	Black																									
S100X150V9TY*	Gold																									
S100X225VA1Y	White			2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1				Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 – 4 AWG											
S100X225VATY*	White																									
S100X225VBTY*	TIA Blue																									
S100X225VCTY*	TIA Brown																									
S100X225VDTY*	TIA Green																									
S100X225VET Y*	TIA Gray																									
S100X225VFTY*	TIA Orange																									
S100X225VGT Y*	TIA Purple																									
S100X225VHTY*	TIA Red																									
S100X225VITY*	TIA Yellow																									
S100X225V0TY*	Black																									
S100X225V9TY*	Gold																									
S100X250VA1Y	White	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	2	5000														
S100X250VATY*													2.50	63.5		1.00	25.4	0.32	8.1	0.48	12.1	6 - 2 AWG				
S100X400VA1Y													4.00	101.6		1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG				
S100X400VATY*																										
S100X650VA1Y													6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 - 250 MCM					
S100X650VATY*																										
S150X225VATY*													2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	8 – 4 AWG					
S150X400VATY*													4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.1	2 – 1 AWG					
S200X150VATY*													2.00	50.8	1.50	38.1	0.50	21.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	2	5000	
S200X225VA1Y																										2.25
S200X225VATY*															2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1				6 – 2 AWG
S200X250VATY*																										
S200X400VA1Y															4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3				2 - 1 AWG
S200X400VATY*																										
S200X650VA1Y															6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4				1/0 - 250 MCM
S200X650VATY*																										

Order number of labels required in multiples of Standard Package Quantity.

\*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## PVDF Self-Laminating Labels

- Self-extinguishing material and recommended alternative to Tedlar®
- Sized specifically for wire and cable applications
- Use thermal transfer hybrid ribbon
- Temperature range: -65°F to 275°F (-54°C to 135°C)
- UL969 recognized File # MH14979; cUL recognized C22.2 No. 0.15.01, File # MH149799



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
S050X150T1T	White	0.50	12.7	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG	8	5000
S075X125T1T		0.75	19.1	1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 – 10 AWG	5	
S100X075T1T		1.00	25.4	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/18 – 14 AWG	4	2500
S100X125T1T				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	12 – 10 AWG		
S100X150T1T				1.50	38.1	0.50	12.7	0.16	4.0	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/ 10 - 6 AWG		
S100X225T1T				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8 – 4 AWG		
S100X400T1T		2.00	50.8	4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG	2	2500
S200X400T1T														500

Tedlar® is a registered trademark of E. I. du Pont de Nemours and Company.


Order number of labels required in multiples of Standard Package Quantity.

\*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## LabelCore™ Fiber Optic Cable Identification System



- Provides a larger labeling surface on small fiber cables and allows legends to be clearly seen
- Sleeves are made of flexible PVC material
- Locate sleeve on straight section of cable at least 2 inches from fiber boot



Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex fiber cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	100
NWSLC-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 1" long, use with labels: S100X225YAJ (Laser/Inkjet); S100X225VAC (LS8E Hand-held Printer); S100X225VATY or S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.

Contact Technical Support at 866.871.4571.

## LabelCore™ Fiber Optic Cable Identification System (continued)

Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC2-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	100
NWSLC2-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 2 inches long, use with labels: S200X225YAJ (Laser/Inkjet) S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.

## Flag Labels

- Halogen-free, white polyester flag-style marker for wire/cable labeling
- Improved legibility and more information on small wires and cables provide clearer, more complete identification
- Innovative design allows the product to be applied as a permanent adhesive label or as a repositionable non-adhesive label
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979;
- cUL recognized C22.2 No. 0.15-01, File # MH14979



Part Number	Width		Height		Print-On Area		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Std. Pkg. Qty. Roll		
	In.	mm	In.	mm	Width	Height	In.	mm	In.	mm				
F100X150AJT	1.00	25.4	1.50	38.1	0.88	22.4	0.75	19.1	0.12	3.1	0.20	5.1	12 – 10 AWG	2500
F100X213AJT			2.13	54.1					0.32	8.1	0.38	9.7	Cat. 5e – Cat. 6	
F100X300AJT			3.00	76.2			2.00	50.8	0.09	2.3	0.28	7.1	8 – 4 AWG	
F100X363AJT			3.63	92.2					0.20	5.1	0.46	11.7	2 – 1 AWG	

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.



## Non-Laminated Vinyl Cloth Labels

- Thin and conformable material with repositionable adhesive allows label to be removed and reused in temporary applications
- Works well on Teflon® coated wires\*
- Use thermal transfer hybrid ribbon
- Temperature range: -40° F to 170° F (-40° C to 77° C)
- UL969 recognized, File # MH14576 and MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576



Part Number	Print-On Area Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N025X075CBT	White	0.25	6.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	7	10000
N025X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N025X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N025X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		
N050X075CBT		0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG		10000
N050X100CBT				1.00	25.4	0.16	4.1	0.24	6.1	10 – 8 AWG		
N050X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N050X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		
N100X075CBT		1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	10000
N100X125CBT				1.25	31.8	0.20	4.1	0.32	8.1	10 – 6 AWG		5000
N100X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		2500
N100X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		2500
N150X075CBT		1.50	38.1	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	1	5000

Order number of labels required in multiples of Standard Package Quantity.  
 Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.  
 \* Teflon® is a registered trademark of E. I du Pont de Nemours and Company

## Non-Laminated Nylon Cloth Labels

- Offer crisp, clear legends with superior legibility
- Used in flat applications and in a wrap format for wire/cable marking
- Use thermal transfer resin ribbon
- Temperature range: -65°F to 275°F (-54°C to 135°C)



Part Number	Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N050X075C1T	White	0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	5	10000
N050X075C2T	Yellow											
N050X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X125C2T	Yellow											
N050X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.5	8 – 2 AWG		
N050X150C2T	Yellow											
N100X075C1T	White	1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	5000
N100X075C2T	Yellow											
N100X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N100X125C2T	Yellow											
N100X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N100X150C2T	Yellow											

Order number of labels required in multiples of Standard Package Quantity.  
 Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## High-Temperature Flame-Retardant Marker Plates

- Used for identification markers in (Class 1E) harsh environments
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer RMER4BL-A or RHER4BL-A resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm		
M200X042FQT	White	2.00	50.8	0.42	10.7	1.22	31.0	500	1
M200X042FQT-B				2000					
M200X080FQT				0.80	20.3			250	
M200X080FQT-B				1000					

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Halogen-Free Flame-Retardant Marker Plates

- Used to identify wires, cables, equipment, and many other applications
- Offer crisp, clear legend with superior legibility and engineered to withstand high temperatures, harsh solvents, oils, and chemicals without over-lamination
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 193°F (-40°C to 90°C)




Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm		
M200X042UPT	White	2.00	50.8	0.42	10.7	1.30	33.0	500	1
M200X042UPT-B				2000					
M200X080UPT				0.80	20.3			500	
M200X080UPT-B				2000					

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Standard Marker Plates

- Non-adhesive and halogen free; used to identify wires, cables, equipment, and many other applications
- Attachable in horizontal or vertical orientation. The 0.5" Plenum rated and 0.33" non-Plenum rated Hook & Loop Cable Ties can be used in hanging position

- Meets the outgassing requirements of ASTM E-595 suitable for use in air handling spaces
- Available in a variety of colors and sizes
- Use thermal transfer resin ribbon
- Temperature range: -58°F to 221°F (-50°C to 105°C)



Part Number	Color	Width		Height		Print-On Area Width		Cable Type	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm			
M200X050Y6T	TIA Yellow	2.00	50.8	0.50	12.7	1.07	27.3	Intermediate Cross Section Cable Ties	500	1
M200X050Y7T	White									
M200X050ACT	TIA Blue									
M200X050AET	TIA Green									
M200X050AFT	TIA Gray									
M200X050AGT	TIA Orange									
M200X050AIT	TIA Red									
M200X100Y6T	TIA Yellow			1.00	25.4	0.80	20.3	Standard Cross Section Cable Ties	2000	
M200X100Y6T-B	White									
M200X100Y7T	White									
M200X100Y7T-B	White									
M200X100ACT	TIA Blue									
M200X100AET	TIA Green									
M200X100AFT	TIA Gray									
M200X100AGT	TIA Orange									
M200X100AIT	TIA Red									
M300X050Y6T	TIA Yellow	3.00	76.2	0.50	12.7	2.07	52.6	Intermediate Cross Section Cable Ties	500	
M300X050Y7T	White									
M300X050ACT	TIA Blue									
M300X050AET	TIA Green									
M300X050AFT	TIA Gray									
M300X050AGT	TIA Orange									
M300X050AIT	TIA Red									
M300X100Y6T	TIA Yellow			1.00	25.4	1.80	45.7	Standard Cross Section Cable Ties	2000	
M300X100Y7T	White									
M300X100ACT	TIA Blue									
M300X100AET	TIA Green									
M300X100AFT	TIA Gray									
M300X100AGT	TIA Orange									
M300X100AIT	TIA Red									

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Military Grade Single-Sided Heat Shrink Labels

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Meet UL Standard 224 with a VW-1 rating for flammability and AMS- DTL-23053/5C (Class 1 and Class 3)
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested for use as an identification marker in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon or white resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1.06, File # 256205



Part Number	Part Number	Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
				In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H050X025H1T*	H050X025H2T	H050X025H3T	H050X025H4T	0.13	3.1	0.50	12.7	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	4	2000	1
H075X025H1T*	H075X025H2T	H075X025H3T	H075X025H4T			0.75	19.1								2	1000	
H100X025H1T*	H100X025H2T	H100X025H3T	H100X025H4T			1.00	25.4								1	500	
H150X025H1T*	H150X025H2T	H150X025H3T	H150X025H4T			1.50	38.1										
H200X025H1T*	H200X025H2T	H200X025H3T	H200X025H4T			2.00	50.8										
H050X034H1T*	H050X034H2T	H050X034H3T	H050X034H4T	0.19	4.7	0.50	12.7	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	4	2000	1
H075X034H1T*	H075X034H2T	H075X034H3T	H075X034H4T			0.75	19.1								2	1000	
H100X034H1T*	H100X034H2T	H100X034H3T	H100X034H4T			1.00	25.4								1	500	
H150X034H1T*	H150X034H2T	H150X034H3T	H150X034H4T			1.50	38.1										
H200X034H1T*	H200X034H2T	H200X034H3T	H200X034H4T			2.00	50.8										
H050X044H1T*	H050X044H2T	H050X044H3T	H050X044H4T	0.25	6.3	0.50	12.7	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	4	2000	1
H075X044H1T*	H075X044H2T	H075X044H3T	H075X044H4T			0.75	19.1								2	1000	
H100X044H1T*	H100X044H2T	H100X044H3T	H100X044H4T			1.00	25.4								1	500	
H150X044H1T*	H150X044H2T	H150X044H3T	H150X044H4T			1.50	38.1										
H200X044H1T*	H200X044H2T	H200X044H3T	H200X044H4T			2.00	50.8										
H050X064H1T*	H050X064H2T	H050X064H3T	H050X064H4T	0.38	9.7	0.50	12.7	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	4	2000	1
H100X064H1T*	H100X064H2T	H100X064H3T	H100X064H4T			1.00	25.4								2	1000	
H200X064H1T*	H200X064H2T	H200X064H3T	H200X064H4T			2.00	50.8								1	500	
H050X084H1T	—	—	—	0.50	12.7	0.50	12.7	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	4	2000	1
H100X084H1T	H100X084H2T	H100X084H3T	H100X084H4T			1.00	25.4								2	1000	
H200X084H1T	H200X084H2T	H200X084H3T	H200X084H4T			2.00	50.8								1	500	
H050X165H1T	—	—	—	1.00	25.4	0.50	12.7	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	4	2000	1
H100X165H1T	H100X165H2T	H100X165H3T	H100X165H4T			1.00	25.4								2	500	
H200X165H1T	H200X165H2T	H200X165H3T	H200X165H4T			2.00	50.8								1	250	
H200X240H1T	H200X240H2T	—	—	1.50	38.1	2.00	50.8	2.40	61.0	0.50	12.7	1.50	38.1	1 AWG – 1000 MCM	1	100	

Order number of labels required in multiples of Standard Package Quantity.  
 \*Available in Bulk packages (5 times Labels Per Roll), add -B to end of part number

## Military Grade Two-Sided Heat Shrink Labels

**PATENTED**

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties of AMS-DTL-23053/5C (Class 1 and Class 3) and UL standard 224 with a VW-1 rating
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B and D, and MIL-STD-202G Method 215K, Solutions A,C and D when printed using resin or hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested as an identification marker for use in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C )
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1-06, File # 256205



Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025H1T-2	H100X025H2T-2	0.13	3.1	1.00	25.4	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	2	1000	1
H100X025H1T-2-B	H100X025H2T-2-B			2.00	50.8									5000	
H200X025H1T-2	H200X025H2T-2			2.00	50.8									500	
H200X025H1T-2-B	H200X025H2T-2-B			2.00	50.8									2500	
H100X034H1T-2	H100X034H2T-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	1
H100X034H1T-2-B	H100X034H2T-2-B			2.00	50.8									5000	
H200X034H1T-2	H200X034H2T-2			2.00	50.8									500	
H200X034H1T-2-B	H200X034H2T-2-B			2.00	50.8									2500	
H100X044H1T-2	H100X044H2T-2	0.25	6.3	1.00	25.4	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	1
H100X044H1T-2-B	H100X044H2T-2-B			2.00	50.8									5000	
H200X044H1T-2	H200X044H2T-2			2.00	50.8									500	
H200X044H1T-2-B	H200X044H2T-2-B			2.00	50.8									2500	
H100X064H1T-2	H100X064H2T-2	0.38	9.7	1.00	25.4	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	1
H100X064H1T-2-B	H100X064H2T-2-B			2.00	50.8									5000	
H200X064H1T-2	H200X064H2T-2			2.00	50.8									500	
H200X064H1T-2-B	H200X064H2T-2-B			2.00	50.8									2500	
H100X084H1T-2	H100X084H2T-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	1
H100X084H1T-2-B	H100X084H2T-2-B			2.00	50.8									5000	
H200X084H1T-2	H200X084H2T-2			2.00	50.8									500	
H200X084H1T-2-B	H200X084H2T-2-B			2.00	50.8									2500	
H100X122H1T-2	H100X122H2T-2	0.75	19.0	1.00	25.4	1.22	31.0	0.25	6.3	0.75	19.0	8 – 4/0 AWG	2	500	1
H200X122H1T-2	H200X122H2T-2			2.00	50.8									250	
H100X165H1T-2	H100X165H2T-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2	500	1
H200X165H1T-2	H200X165H2T-2			2.00	25.4									250	

Order number of labels required in multiples of Standard Package Quantity.

## Halogen-Free Two-Sided Heat Shrink Labels

**PATENTED**

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet SAE-AS5942, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Meet BS6853; 1999 Vehicle Category 1A for burning behavior and toxic gas emissions; Smoke Density Class II
- Shrink ratio 2:1
- Use thermal transfer hybrid ribbon
- Temperature range: -22°F to 221°F (-30°C to 105°C)



Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025HFT-2	H100X025HGT-2	0.13	3.1	1.00	25.4	0.25	6.4	0.06	1.5	0.13	3.3	22 – 18 AWG	2	1000	1
H200X025HFT-2	H200X025HGT-2			2.00	50.8								1	500	
H100X034HFT-2	H100X034HGT-2	0.19	4.7	1.00	25.4	0.34	8.6	0.09	2.3	0.19	4.8	18 – 12 AWG	2	1000	
H200X034HFT-2	H200X034HGT-2			2.00	50.8								1	500	
H100X044HFT-2	H100X044HGT-2	0.25	6.4	1.00	25.4	0.44	11.1	0.13	3.3	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HFT-2	H200X044HGT-2			2.00	50.8								1	500	
H100X064HFT-2	H100X064HGT-2	0.38	9.7	1.00	25.4	0.64	16.2	0.19	4.8	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HFT-2	H200X064HGT-2			2.00	50.8								1	500	
H100X084HFT-2	H100X084HGT-2	0.50	12.7	1.00	25.4	0.84	21.3	0.25	6.4	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HFT-2	H200X084HGT-2			2.00	50.8								1	500	
H100X165HFT-2	H100X165HGT-2	1.00	25.4	1.00	25.4	1.65	41.9	0.50	12.7	1.00	25.4	8 AWG – 500 MCM	2	500	
H200X165HFT-2	H200X165HGT-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.

## Fluid-Resistant Two-Sided Heat Shrink Labels

**PATENTED**

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Cross-linked, semi-rigid, fluid-resistant, shrinkable polyolefin material
- Available in yellow only
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties AMS-DTL-23053/6 Class 1 and NF F00-608 Class A and H when printed with resin thermal transfer ribbons

- Meet SAE-AS5942, MIL-STD-883F Method 2015.13 Solutions A and D, and MIL-STD-202G Method 215K, Solutions A and D when printed with resin thermal transfer ribbons
- Shrink ratio 3:1
- Use thermal transfer RMER4BL-C resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X034HST-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	1
H200X034HST-2			2.00	50.8								1	500	
H100X044HST-2	0.25	6.4	1.00	25.4	0.44	11.1	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HST-2			2.00	50.8								1	500	
H100X064HST-2	0.38	9.7	1.00	25.4	0.64	16.2	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HST-2			2.00	50.8								1	500	
H100X084HST-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HST-2			2.00	50.8								1	500	
H100X165HST-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2	1000	
H200X165HST-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.



## Raised Panel Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
C120X150APT-22	White	1.20	30.5	1.50	38.1	0.45	11.4	0.87	22.0	3	500
C120X150A8T-22	Yellow										
C120X150AST-22	Green										
C120X150AWT-22	Red										
C120X150A0T-22	Black										
C120X190APT-22	White	1.90	48.3	0.85	21.6	1.18	30.0	2			
C120X190A8T-22	Yellow										
C120X190AST-22	Green										
C120X190AWT-22	Red										
C120X190A0T-22	Black										
C180X180APT-30	White	1.80	45.7	1.80	45.7	0.36	9.1	1.18	30.0	2	
C180X180A8T-30	Yellow										
C180X180AST-30	Green										
C180X180AWT-30	Red										
C180X180A0T-30	Black										
C240X240APT-30	White	2.40	61.0	2.40	61.0	0.90	22.9	1			
C240X240A8T-30	Yellow										
C240X240AST-30	Green										
C240X240AWT-30	Red										
C240X240A0T-30	Black										

Order number of labels required in multiples of Standard Package Quantity.  
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Raised Panel Push Button Over-Laminate Labels

- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Hole Diameter		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm		
C120X150YK-22	Clear	1.20	30.5	1.50	38.1	0.87	22.0	3	500
C120X190YK-22				1.90	48.3				
C180X180YK-30		1.80	45.7	1.80	45.7	1.18	30.0	2	
C240X240YK-30		2.40	60.9	2.40	60.9	1.18	30.0	1	

Order number of labels required in multiples of Standard Package Quantity.

## Raised Panel Half Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
C180X130APT-30H	White	1.80	45.7	1.30	33.0	0.73	18.5	1.18	30.0	1	500
C240X200APT-30H		2.40	61.0	2.00	50.8	1.43	36.3				

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Raised Panel Component Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance, and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C100X050APT	White	1.00	25.4	0.50	12.7	3	500
C100X050A8T	Yellow						
C100X050AST	Green						
C100X050AUT	Orange						
C100X050AWT	Red						
C100X050A0T	Black						
C100X050AMT	Silver	1.25	31.8	0.30	7.6		
C125X030APT	White						
C125X030A0T	Black						
C170X090APT	White	1.70	43.2	0.90	22.9		
C170X090A8T	Yellow						
C170X090AST	Green						
C170X090AWT	Red						
C170X090AMT	Silver						
C200X100APT	White	2.00	50.8	1.00	25.4		
C200X100A8T	Yellow						
C200X100AST	Green						
C200X100AUT	Orange						
C200X100AWT	Red						
C200X100A0T	Black						
C200X100AMT	Silver	2.52	64.0	0.30	7.6		
C252X030APT	White						
C252X030A0T	Black	3.00	76.2	1.00	25.4	1	
C300X100APT	White						
C300X100A8T	Yellow						
C300X100AUT	Orange						
C300X100AWT	Red						
C300X100A0T	Black			2.50	63.5		
C300X250APT	White						
C300X250A8T	Yellow						
C300X250AST	Green						
C300X250AUT	Orange						
C300X250AWT	Red						
C300X250A0T	Black	3.50	88.9	3.00	76.2		
C300X250AMT	Silver						
C350X300APT	White						
C350X300A8T	Yellow						
C350X300AUT	Orange						
C350X300A0T	Black	3.79	96.3	0.30	7.6		
C379X030APT	White						
C379X030AQT	Blue						
C379X030AWT	Red						
C379X030A0T	Black	4.00	101.6	1.00	25.4		
C400X100APT	White						
C400X100A8T	Yellow						
C400X100AST	Green						
C400X100AUT	Orange						
C400X100AWT	Red						
C400X100A0T	Black						
C400X100AMT	Silver						

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Contact Technical Support at 866.871.4571.

## Raised Panel Component Over-Laminate Labels


- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm		
C100X050YK	Clear	1.00	25.4	0.50	12.7	1	500
C170X090YK		1.70	43.2	0.90	22.9		
C200X100YK		2.00	50.8	1.00	25.4		
C300X100YK		3.00	76.2	1.00	25.4		
C300X250YK				2.50	63.5		
C350X300YK		3.50	88.9	3.00	76.2		
C400X100YK		4.00	101.6	1.00	25.4		

Order number of labels required in multiples of Standard Package Quantity.

## Raised Panel Pre-Printed Emergency Stop Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14576; cUL recognized C22.2 No. 0.15.01, File # MH14576



Part Number	Color	Diameter		Hole Diameter		Std. Pkg. Qty.
		In.	mm	In.	mm	
C235A8-30-ES	Black on Yellow	2.35	60.0	1.18	30.0	25
C235AW-30-ES	White on Red					
C350A8-30-ES	Black on Yellow	3.50	89.0			
C350AW-30-ES	White on Red					

Order number of labels required in multiples of Standard Package Quantity.

## Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not easily stretch or tear
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979




Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.				
		In.	mm	In.	mm						
C025X025YJT	White	0.25	6.4	0.25	6.4	12	10000				
C038X038YJT		0.38	9.7	0.38	9.7	7					
C050X044YJT		0.50	12.7	0.44	11.2	5					
C060X020YJT		0.60	15.2	0.20	5.1	3					
C075X025YJT		0.75	19.1	0.25	6.4						
C075X025YMT	Silver										
C080X020YJT	White	0.80	20.3	0.20	5.1	3		5000			
C090X025YJT		0.90	22.9	0.25	6.4						
C100X025YJT		1.00	25.4	0.25	6.4						
C100X038YJT				0.38	9.7						
C100X050YJT				0.50	12.7						
C100X050YKT	Clear										
C100X050YMT	Silver										
C125X038YJT	White	1.25	31.8	0.38	9.7	3	10000				
C150X050YJT		1.50	38.1	0.50	12.7						
C150X075YJT				0.75	19.1						
C150X075YMT	Silver										
C160X020YJT	White	1.60	40.6	0.20	5.1	3		5000			
C200X025YJT		2.00	50.8	0.25	6.4						
C200X038YJT				0.38	9.7						
C200X050YJT				0.50	12.7						
C200X100YJT		Clear	1.00	25.4	1.00				25.4	1	2500
C200X100YKT											
C200X100YMT											
C275X125YJT	White	2.75	69.9	1.25	31.8	1	5000				
C275X125YMT	Silver										
C300X025YJT	White	3.00	76.2	0.25	6.4						
C300X038YJT				0.38	9.7						
C300X100YJT				1.00	25.4						
C300X100YMT				Silver							
C300X200YJT				White	2.00			50.8			
C300X200YMT	Silver										
C350X100YJT	White	3.50	88.9	1.00	25.4			1	2500		
C400X100YJT		4.00	101.6							2.00	50.8
C400X200YJT						2.00	50.8				
C400X200YMT						Silver					
C400X300YJT		White	4.00			101.6	3.00			76.2	1
C400X400YJT	4.00			101.6							
C400X600YJT	6.00			152.4							

Order number of labels required in multiples of Standard Package Quantity.  
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Contact Technical Support at 866.871.4571.

## Super-Tack Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not stretch or easily tear; and has high-tack permanent adhesive
- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware
- Meets DIN 40050-9, IP69K for washdown applications
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Type of Application	Labels Per Row	Std. Pkg. Qty.							
		In.	mm	In.	mm										
C061X030YPT	White	0.61	15.5	0.30	7.6	1-port	4	2500							
C100X050YPT		1.00	25.4	0.50	12.7	general identifier	3	10000							
C125X030YPT		1.25	31.8	0.30	7.6	2-port									
C138X019YPT	Black	1.38	35.1	0.19	4.8	module									
C138X019Y0T															
C188X030YPT	White	1.88	47.8	0.30	7.6	3-port									
C200X100YPT															
C200X100Y0T	Black	2.00	50.8	1.00	25.4	general identifier									
C252X030YPT	White	2.52	64.0	0.30	7.6	4-port			1, 2, 3, or 4-port	2500					
C252X030YPT-P*															
C252X030YQT-P*						TIA Blue									
C252X030YRT-P*						TIA Brown									
C252X030YST-P*						TIA Green									
C252X030YTT-P*						TIA Gray									
C252X030YUT-P*						TIA Orange									
C252X030YVT-P*						TIA Purple									
C252X030YWT-P*						TIA Red									
C252X030Y0T-P*						Black									
C252X030Y8T-P*						TIA Yellow									
C252X030Y9T-P*						Gold									
C261X030YPT						White	2.61	66.3			0.30	7.6	4-port	1	
C275X125YPT															
C275X125Y0T	Black	2.75	69.9	1.25	31.8	general identifier									
C288X030YPT	White	2.88	73.2	0.30	7.6	5-port									
C300X200YPT		3.00	76.2	2.00	50.8	general identifier									
C315X030YPT		3.15	80.0	0.30	7.6	5-port									
C379X030YPT		Black	3.79	96.3	0.30	7.6			6-port	1, 2, 3, 4, 5 or 6-port					
C379X030YPT-P*															
C379X030YQT-P*									TIA Blue						
C379X030YRT-P*	TIA Brown														
C379X030YST-P*	TIA Green														
C379X030YTT-P*	TIA Gray														
C379X030YUT-P*	TIA Orange														
C379X030YVT-P*	TIA Purple														
C379X030YWT-P*	TIA Red														
C379X030Y0T-P*	Black														
C379X030Y8T-P*	TIA Yellow														
C379X030Y9T-P*	Gold														
C400X200Y8T	Yellow	4.00	101.6	2.00	50.8	general identifier		1000							
C400X300YPT	White			3.00	76.2			2500							

\*Label is perforated to be used in 1, 2, 3, 4, or 6-Port position applications.  
 Order number of labels required in multiples of Standard Package Quantity.  
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Tedlar® Component Labels

- Self-extinguishing and ideal for labeling high-temperature areas
- Meet Federal Motor Vehicle Safety Standard (FMVSS-302) for flammability
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 225°F (-40°C to 106°C); tests at 275°F have shown acceptable results



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C060X020TJT	White	0.60	15.2	0.20	5.1	3	10000
C090X025TJT		0.90	22.9	0.25	6.4		
C100X038TJT		1.00	25.4	0.38	9.7		
C100X050TJT				0.50	12.7		
C125X038TJT		1.25	31.8	0.38	9.7	1	2500
C200X038TJT		2.00	50.8				1.00
C200X100TJT				1.00	25.4	2500	
C300X038TJT				3.00	76.2	0.38	9.7

Tedlar® is a registered trademark of E.I. du Pont de Nemours and Company. Order number of labels required in multiples of Standard Package Quantity. Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Tamper-Evident Polyester Component Labels

- Leaves a checkerboard of silver material allowing you to see if label has been tampered with
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C075X025AAT	Silver	0.75	19.1	0.25	6.4	3	10000
C100X050AAT		1.00	25.4	0.50	12.7		
C200X100AAT		2.00	50.8	1.00	25.4	1	2500
C275X125AAT		2.75	69.9	1.25	31.8		

Order number of labels required in multiples of Standard Package Quantity. Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Non-Adhesive Polyester Component Labels

- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware
- Use thermal transfer resin ribbon
- Temperature range: -10°F to 302°F (-23°C to 150°C)



Part Number	Color	Width		Height		Application	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm			
C150X030Y1T	White	1.50	38.1	0.30	7.6	3-port identifier	2	1000
C195X040Y1T		1.95	49.5	0.40	10.2	Single-gang faceplate		
C261X035Y1T		2.61	66.3	0.35	8.9	4-port identifier		
C288X040Y1T		2.88	73.2	0.40	10.2	Double-gang faceplate		
C390X030Y1T		3.90	99.1	0.30	7.6	6-port identifier		
C750X050Y1T		7.50	190.5	0.50	12.7	110 block		
C788X050Y1T		7.88	200.2	0.50	12.7	GP6™ Punchdown System		

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Vinyl Cloth Component Labels

- Ideal for temporary marking of chips, boards, and ICs
- Removable without leaving any residue
- Pliable material is suitable for rough texture surfaces
- Use thermal transfer hybrid ribbon
- Temperature range: 50°F to 170°F (10°C to 77°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.			
		In.	mm	In.	mm					
C050X044CBT	White	0.50	12.7	0.44	11.2	5	10000			
C060X020CBT		0.60	15.2	0.20	5.1	3				
C075X025CBT		0.75	19.1	0.25	6.4					
C100X025CBT		1.00	25.4					0.38	9.7	
C100X038CBT				0.50	12.7					
C100X050CBT				1	50.8	101.6		0.75	19.1	5000
C150X075CBT		1.50	38.1					0.75	19.1	5000
C160X020CBT		1.60	40.6					0.20	5.1	10000
C200X050CBT		2.00	50.8					0.50	12.7	5000
C400X100CBT		4.00	101.6	1.00	25.4	2500				

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.



## Polyimide Component Labels

- Ideal for electronic components and internal circuitry applications
- Intended for applications requiring solvent and high-temperature resistance performance, such as the wave solder process

- Use thermal transfer RMER4BL-C or RHER4BL-C resin ribbon on white polyimide
- Use thermal transfer hybrid ribbon on tan polyimide
- Temperature range: -40°F to 350°F (-40°C to 177°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C025X025KBT	White	0.25	6.4	0.25	6.4	12	10000
C025X025KCT	Tan						
C038X038KBT	White	0.38	9.7	0.38	9.7	7	
C038X038KCT	Tan						
C050X013KBT	White	0.50	12.7	0.13	3.3	5	
C050X013KCT	Tan						
C050X020KBT	White			0.20	5.1		
C050X044KBT				0.44	11.2		
C050X044KCT	Tan						
C060X020KBT	White	0.60	15.3	0.20	5.1	3	
C060X020KCT	Tan						
C065X019KBT	White	0.65	16.5	0.19	4.8		
C065X019KCT	Tan						
C075X025KBT	White	0.75	19.1	0.25	6.4		
C075X025KCT	Tan						
C080X020KBT	White	0.80	20.3	0.20	5.1		
C080X020KCT	Tan						
C090X025KBT	White	0.90	22.9	0.25	6.4		
C090X025KCT	Tan						
C100X019KBT	White	1.00	25.4	0.19	4.8		
C100X019KCT	Tan						
C100X025KBT	White			0.25	6.4		
C100X025KCT	Tan						
C100X038KBT	White			0.38	9.7		
C100X038KCT	Tan						
C125X025KBT	White	1.25	31.8	0.25	6.4		2
C125X025KCT	Tan						
C150X025KBT	White	1.50	38.1	0.25	6.4		5000
C150X025KCT	Tan						
C160X020KBT	White	1.60	40.6	0.20	5.1		10000
C160X020KCT	Tan						
C200X025KBT	White	2.00	50.8	0.25	6.4		1
C200X025KCT	Tan						
C200X038KBT	White			0.38	9.7		
C300X025KBT							
C300X025KCT	Tan	3.00	76.2	0.25	6.4	5000	

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Contact Technical Support at 866.871.4571.

## Paper Component Labels

- General purpose material
- Use thermal transfer hybrid ribbon

- Temperature range: -65°F to 160°F (-54°C to 71°C)
- UL969 recognized, File # MH14576 and File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C075X025PBT	White	0.75	19.1	0.25	6.4	3	10000
C100X050PBT		1.00	25.4	0.50	12.7		
C150X075PBT		1.50	38.1	0.75	19.1		
C200X100PBT		2.00	50.8	1.00	25.4	1	5000
C300X200PBT		3.00	76.2	2.00	50.8		2500
C400X100PBT		4.00	101.6	1.00	25.4		1000
C400X200PBT				2.00	50.8		2500
C400X300PBT				3.00	76.2		1000
C400X500PBT				5.00	127.0		2500
C400X600PBT				6.00	152.4		1000

Order number of labels required in multiples of Standard Package Quantity.  
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Reflective Continuous Tapes

- Used for illuminating or highlighting a range of objects
- Offer crisp, clear legends with superior legibility
- Conformable material for flat applications and safety and facility identification
- Can be over-laminated to increase durability (see page 28)

- Use thermal transfer resin ribbon
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Length		Std. Pkg. Qty. (Roll)
		In.	mm	Ft.	m	
T100X000RP1	White	1.00	25.4	50.0	15.2	1
T100X000RU1	Orange					
T100X000RW1	Red					
T100X000RX1	Yellow					
T200X000RP1	White	2.00	50.8			
T200X000RU1	Orange					
T200X000RW1	Red					
T200X000RX1	Yellow					
T300X000RP1	White	3.00	76.2			
T400X000RP1	White					
T400X000RQ1	Blue	4.00	101.6			
T400X000RU1	Orange					
T400X000RW1	Red					
T400X000RX1	Yellow					

Order number of labels required in multiples of Standard Package Quantity.

## Continuous Tapes

- Offer crisp, clear legends with superior legibility
- Conformable material for flat applications and safety and facility identification
- Can be over-laminated to increase durability (see page 28)
- Use thermal transfer resin ribbon
- For white, black, clear, blue, and yellow vinyl continuous tapes only: UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979




Part Number	Color	Material	Temperature Range	Width		Length		Std. Pkg. Qty. (Roll)							
				In.	mm	Ft.	m								
T024X000FJT*	White	Polyolefin	-40°F to 180°F (-40°C to 82°C)	0.24	6.1										
T031X000FJT*				0.31	7.9										
T038X000FJT*				0.38	9.7										
T050X000FJT*				0.50	12.7										
T100X000VP1Y															
T100X000VQ1Y	Blue	Vinyl	-58°F to 176°F (-50°C to 80°C)	1.00	25.4										
T100X000VS1Y	Green														
T100X000VU1Y	Orange														
T100X000VW1Y	Red														
T100X000VX1Y	Yellow														
T100X000VY1Y	Black														
T100X000YK1	Clear	Polyester	-40°F to 302°F (-40°C to 150°C)												
T200X000VP1Y	White	Vinyl	-58°F to 176°F (-50°C to 80°C)	2.00	50.8	100.0	30.5	1							
T200X000VQ1Y	Blue														
T200X000VR1Y	Brown														
T200X000VS1Y	Green														
T200X000VT1Y	Gray														
T200X000VU1Y	Orange														
T200X000VV1Y	Purple														
T200X000VW1Y	Red														
T200X000VX1Y	Yellow														
T200X000VY1Y	Black														
T200X000YK1	Clear								Polyester	-40°F to 302°F (-40°C to 150°C)					
T400X000VP1Y	White								Vinyl	-58°F to 176°F (-50°C to 80°C)	4.00	101.6			
T400X000VQ1Y	Blue														
T400X000VR1Y	Brown														
T400X000VS1Y	Green														
T400X000VT1Y	Gray														
T400X000VU1Y	Orange														
T400X000VV1Y	Purple														
T400X000VW1Y	Red														
T400X000VX1Y	Yellow														
T400X000VY1Y	Black														
T400X000YK1	Clear	Polyester	-40°F to 302°F (-40°C to 150°C)												

Order number of rolls required in multiples of Standard Package Quantity.

\*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

## Super-Tack Polyester Continuous Tapes

- Thermal transfer printable continuous tape format
- Super-tack polyester has ultra-aggressive adhesive
- Ideal for rough, textured, and coated surfaces
- Applications include rack unit labeling, cabinets, cable tray, pathways, control panels, enclosures, pipes, and much more
- Meets DIN 40050-9, IP69K for washdown applications.
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Material	Width		Length		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	m	
T038X000Y01	Black	Polyester	0.38	9.7	100.0	30.5	1
T038X000YP1	White						
T050X000Y01	Black						
T050X000YP1	White						
T100X000Y01	Black						
T100X000Y81	Yellow						
T100X000YP1	White						
T100X000YQ1	Blue						
T100X000YS1	Green						
T100X000YU1	Orange						
T100X000YW1	Red						
T200X000Y01	Black						
T200X000Y81	Yellow						
T200X000YP1	White						
T200X000YQ1	Blue						
T200X000YS1	Green						
T200X000YU1	Orange						
T200X000YW1	Red						
T400X000Y01	Black						
T400X000Y81	Yellow						
T400X000YP1	White						
T400X000YQ1	Blue						
T400X000YS1	Green						
T400X000YU1	Orange						
T400X000YW1	Red						

Order number of labels required in multiples of Standard Package Quantity.

## Non-Printable Clear Over-Laminate Continuous Tapes

- Over-laminates can be used for additional protection over the 2" and 4" continuous tapes
- When over-laminates are used with Super-Tack Polyester Labels, the labels meet DIN 40050-9, IP69K for washdown applications
- Temperature range: -40°F to 302°F (-40°C to 150°C)

Part Number	Color	Material	Width		Length		Std. Pkg. Qty.
			In.	mm	Ft.	m	
T225X000YK1	Clear	Polyester	2.25	57.2	100.0	30.5	1
T425X000YK1			4.25	107.9			

Order number of labels required in multiples of Standard Package Quantity.

## Super-Tack Polyester Arc Flash Labels

- Provide employees with the highest degree of safety through proper identification and communication
- Detailed formats compliant with NFPA 70E standard for Arc Flash labeling
- Clearly visible and recognizable hazard information to communicate arc flash hazards present
- Meets DIN 40050-9, IP69K for washdown applications
- Labels are constructed of durable polyester designed to withstand UV exposure, outdoor use, water and abrasion
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



C200X400A51



C200X400YZ1




C400X400A51



C400X400YZ1



C400X600A51



C400X600YX1



C400X600YZ1

Part Number	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
	In.	mm	In	mm		
C200X400A51	2.00	50.8	4.00	101.6	Polyester safety label, WARNING header orange and black, 250 labels per roll.	1
C200X400YZ1					Polyester safety label, DANGER header red and white, 250 labels per roll.	
C400X400A51	4.00	101.6	6.00	152.4	Polyester safety label, WARNING header orange and black, 250 labels per roll.	
C400X400YZ1					Polyester safety label, DANGER header red and white, 250 labels per roll.	
C400X600A51					Polyester safety label, WARNING header orange and black, 100 labels per roll.	
C400X600YX1					Polyester safety label, orange header, 100 labels per roll.	
C400X600YZ1					Polyester safety label, DANGER header red and white, 100 labels per roll.	

Order number of labels required in multiples of Standard Package Quantity

## Raised Panel Arc Flash Labels

- Super-Tack adhesive provides strong holding power for rough, textured, and powered-coated surfaces
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposures)
- Meet ASTM D3389 standard for abrasion resistance, and also meets solar application standards
- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979



C400X400AOT



C400X400ANT

Part Number	Color	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
		In.	mm	In	mm		
C400X400ANT	Orange	4.00	101.6	4.00	101.6	Raised Panel Safety Label, WARNING header, White and Orange/Black	1
	White						
C400X400AOT	Red					Raised Panel Safety Label, DANGER header, White and Red/Black	
	White						

Order number of labels required in multiples of Standard Package Quantity

Contact Technical Support at 866.871.4571.

## Super-Tack Polyester Arc Flash Continuous Tapes



T400X000YX1



T400X000A91

Part Number	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
	In.	mm	Ft	M		
T400X000YX1	4.00	101.6	50.0	15.2	Polyester arc flash continuous tape, orange header.	1
T400X000A91					Polyester arc flash continuous tape, red header.	

Order number of labels required in multiples of Standard Package Quantity

## Super-Tack Polyester Facility Identification Labels

- Facility Identification created quickly to comply with workplace safety regulations contributing to the protection of employees and equipment from unexpected hazards
- Meets DIN 40050-9, IP69K for washdown applications
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



C400X600A41



C400X600A61



C400X600AX1



C400X600AY1



C400X600AZ1



C400X600Y81

Part Number	Width		Height		Part Description	Labels Per Row	Std. Pkg. Qty. (Roll)
	In.	mm	In	mm			
C400X600A41	4.00	101.6	6.00	152.4	Polyester safety label, DANGER header, red and black/white, 100 labels per roll.	1	1
C400X600A61					Polyester safety label, CAUTION header, yellow/black, 100 labels per roll.		
C400X600AX1					Polyester safety label, blue/white, NOTICE header, 100 labels per roll.		
C400X600AY1					Polyester safety label, green/ white, SAFETY FIRST header, 100 labels per roll.		
C400X600AZ1					Polyester safety label, yellow header, 100 labels per roll.		
C400X600Y81					Polyester safety label, yellow, 100 labels per roll.		


Order number of labels required in multiples of Standard Package Quantity

## Polyester Photoluminescent Tapes

- Used to mark egress routes, fire alarms, and fire equipment
- Clearly visible for up to ten hours after power is lost
- Absorbs energy from ambient light and releases this energy in the form of a glow when power is lost
- Can be over-laminated to increase durability (see page 28)
- Use thermal transfer resin ribbon
- Temperature range: 40°F to 230°F (4.4°C to 110°C)
- UL969 recognized, File # MH14979



Normal Lighting



Blackout

Part Number	Color	Width		Length		Std. Pkg. Qty. (Roll)
		In.	mm	Ft	M	
T200X000Y2T	Photoluminescent	2.00	50.8	15.0	4.5	1
T400X000Y2T		4.00	101.6			

Order number of labels required in multiples of Standard Package Quantity

## Raised Panel Solar Labels


- Print customized labels for solar applications
- Strong holding power for rough, textured, and coated surfaces
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposures)
- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C200X100AWT	Red	2.00	50.8	1.00	25.4	1	500
C300X250AWT		3.00	76.2	2.50	63.5		
C400X100AWT		4.00	101.6	1.00	25.4		

Order number of labels required in multiples of Standard Package Quantity

## Super-Tack Polyester Solar Labels



- Solar Labels are designed to meet required safety standards for PV installation labeling.
- Certain labels leave blank spaces where variable thermal transfer printing can be added when specific on-site power and series data is required.
- Meets DIN 40050-9, IP69K for washdown applications
- This product solution has an optional clear over-laminate to function in harsh environments.

- All labels are outdoor rated and are designed to have high resistance to direct UV exposure.
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width		Height		Application	Legend	Std. Pkg. Qty. (Roll)	
		In.	mm	In.	mm				
C400X200SP1-AD	White on Red	4.00	101.6	2.00	50.8	AC Disconnect	VOLTAGE AND CURRENT RATINGS	50	
C400X400SP1-ASM				4.00	101.6	AC Photovoltaic Module			VOLTAGE CURRENT AND POWER RATINGS
C400X400SP1-DD						DC Disconnect			VOLTAGE AND CURRENT RATINGS
C400X400SP1-DSM						DC Photovoltaic Module			VOLTAGE CURRENT AND POWER RATINGS
C400X400SP1-PS						Photovoltaic Power Source			VOLTAGE AND CURRENT RANTINGS
C600X175SP1-AD	6.00	152.4	1.75	44.5	AC Disconnect		PHOTOVOLTAIC - AC DISCONNECT		
C600X175SP1-DD					DC Disconnect		PHOTOVOLTAIC - DC DISCONNECT		

Order number of labels required in multiples of Standard Package Quantity

## Over-Laminate Labels

Part Number	Color	Width		Height		Application	Std. Pkg. Qty.
		In.	mm	In.	mm		
C300X150SL1-OL	Clear	1.50	38.1	3.00	76.2	Additional Abrasion and UV Protection	250
C400X200SL1-OL		2.00	50.8	4.00	101.6	Additional Abrasion and UV Protection	
C400X400SL1-OL		4.00	101.6			Additional Abrasion and UV Protection	
C600X175SL1-OL		1.75	44.5	6.00	152.4	Additional Abrasion and UV Protection	

Order number of labels required in multiples of Standard Package Quantity

## Reflective Continuous Tapes for Solar Applications



- Used for illuminating or highlighting a range of objects
- Conformable material for flat applications and safety and facility identification
- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 180°F (-40°C to 82°C)

- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979

Part Number	Color	Material	Width		Height		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	M	
T400X000RW1	Red	Polyester	4.00	101.6	50.0	15.2	1

Order number of labels required in multiples of Standard Package Quantity




## Easy-Mark™ Labeling Software

**PATENTED**

- Quickly and easily generate labels
- Market specific labeling application tools assist in creation of identification solutions for data centers, network applications, panel shops, and construction and maintenance applications
- Saves time and money (up to 75%) with features such as WYSIWYG user interface, data import, symbol import, and pre-loaded formats
- Site license available for up to five additional installs per license
- Upgrades available at [www.panduit.com](http://www.panduit.com)

- 64 MB hard drive space and 64 MB RAM (256 MB RAM recommended)
- Windows 2000, XP, Vista, 7, 8 or 10
- Mouse or compatible pointing device
- Microsoft.NET Framework 2.0 or higher
- CD-ROM Drive or USB Port

System Requirements:



Part Number	Color	Std Pkg. Qty	Std. Ctn. Qty.
<b>PROG-EMCD3</b>	Easy-Mark™ Labeling Software, CD-ROM	1	10
<b>PROG-EM2GO</b>	Easy-Mark™ Portable Application, USB Flash Drive		


^Windows is a registered trademark of Microsoft Corp. in the United States and/or other countries.

## CAD-Connect™ Labeling Software

- Facilitates quick and easy organization of identifiers from CAD for printing within Easy-Mark™ Labeling Software
- Easily captures and organizes CAD data for future use and documentation
- Saves time and reduces errors by utilizing identifiers previously created in CAD files to eliminate manual entry of data into labeling software
- Compatible with full versions of AutoCAD\* 2002 to 2016 and Visio version 2002 or newer
- Exports to alternative formats such as Excel^ (XLS) or Text (CSV) files for future use and documentation
- Upgrades available at [www.panduit.com](http://www.panduit.com)

System Requirements:

- 64 MB hard drive space and 64 MB RAM (256 MB RAM recommended)
- Windows 2000, XP, Vista, 7, 8 or 10
- Mouse or compatible pointing device
- Microsoft.NET Framework 2.0 or higher
- CD-ROM Drive



Part Number	Color	Std Pkg. Qty	Std. Ctn. Qty.
<b>PROG-CCCD</b>	CAD-Connect™ Labeling Software, including Easy-Mark™ Labeling Software, CD-ROM.	1	10

^Visio, Windows and EXCEL are registered trademarks of Microsoft Corp. in the United States and/or other countries.

\*AutoCAD is a registered trademark of Autodesk, Inc.

## TDP43ME Desktop Printer and Accessories

- Creates durable, crisp, clear legends and graphics that offer superior legibility
- Prints durable legends for harsh industrial environments
- Fine resolution for small type characters and images
- Easy-Mark™ Labeling Software included with printer
- Up to 4 inches per second print speed
- Auto-sensing label gap and black mark sensors
- One-button operation, and automatic self test
- Connects quickly and easily to PC, and offers connectivity flexibility to print by USB, parallel serial, or Ethernet
- Easy ribbon loading reduces printer down time
- Able to connect to a network for sharing capability
- UL60950 listed, File # E165747



Part Number	Part Description	Std. Pkg. Qty.
TDP43ME	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, and driver disk; for use in North America	1
TDP43ME/E	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, EuroPlug cord, USB cable, user manual, quick start card, and driver disk; for use outside North America	
TDP43ME-KIT	TDP43ME printer kit. Includes: printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, TDP43ME-RS Roll Stand, TDP43ME-CASE, one roll of S100X150VATY labels, and driver disk; for use in North America	
TDP43ME/E-KIT	TDP43ME/E printer kit. Includes: printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with EuroPlug cord, USB cable, user manual, quick start card, TDP43ME-RS Roll Stand, TDP43ME-CASE, one roll of S100X150VATY labels, and driver disk; for use outside North America	
TDP43ME-AC	Replacement AC power adapter with power cord (US cord only).	
TDP43ME-CASE	Hardside carrying case accommodates printer, AC power adapter, ribbons, printer cable, external roll stand, labels, and tools.	
TDP43ME-CUTTER	Optional power/automatic cutter for TDP43ME thermal transfer desktop printer; easy to install for automatic cutting of labels.	
TDP43ME-RS	External label roll stand for TDP43ME printer; used to rear feed labels that are supplied on 3" cores.	
TDP43ME-SPINDLE	Replacement ribbon spindle for TDP43ME Thermal Transfer Desktop Printer, Package of Two Spools.	
PTR-CLN	Printer cleaning kit – contains bottle of cleaning solution with MSDS, cleaning pen, swabs, alcohol wipes, and cleaning instructions.	

## TDP43ME Desktop Printer Ribbons

Part Number	Part Description	Width		Length		Std. Pkg. Qty.
		In.	mm	Ft.	m	
RMEH4BL*	Black hybrid thermal transfer ribbon. Use with heat shrink, self-laminating, Turn-Tell®, tan polyimide labels, and vinyl cloth labels.	4.25	108.0	300.0	91.4	1
RMER4BL*	Black resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4BU	Blue resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4GR	Green resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4RD	Red resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4WH*	White resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4BL-A	Black resin thermal transfer ribbon. Use with high-temperature marker plates.					
RMER4BL-C	Black resin thermal transfer ribbon. Use with fluid-resistant heat shrink labels and white polyimide labels.					

Order number of ribbons required in multiples of Standard Package Quantity.

\*For 2.5" wide ribbons, replace 4 in part number with 2. For example, the part number of a 2.5" wide black hybrid thermal transfer ribbon is RMEH2BL.

## TDP43HE and TDP46HE Desktop Printers and Accessories

- Convenient, easy setup; quickly begin producing labels
- Durable, clear communication through superior legibility
- Print small, fine characters and high-quality images and bar codes
- Allow continuous use in construction, industrial, and harsh environments
- Reduce time required to switch between label styles
- Fast label production without sacrificing print quality
- Easy-Mark™ Labeling Software included with printer
- Up to 8 inches per second print speed
- Connect quickly and easily to PC, and offers connectivity flexibility to print by USB, parallel, Ethernet or serial
- Available with 300 or 600 dots per inch print resolution
- Able to connect to a network for sharing capability
- UL60950 listed, File # E165747



Part Number	Part Description	Std Pkg. Qty
TDP43HE	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk and US power cord; for use in North America.	1
TDP43HE/E	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and the following power cords: EuroPlug, Swiss, UK, and Japan JIS 8303 3-pin; for use outside North America.	
TDP46HE	600 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and US power cord; for use in North America.	
TDP46HE/E	600 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and the following power cords: Europlug, Swiss, UK, and Japan JIS 8303 3-pin; for use outside North America.	
PTR-CLN	Printer cleaning kit - contains bottle of cleaning solution with MSDS, cleaning pen, swabs, alcohol wipes, and cleaning instructions.	

## TDP43HE and TDP46HE Desktop Printer Ribbons

Part Number	Part Description	Width		Length		Std. Pkg. Qty.
		In.	mm	Ft.	m	
RHEH4BL	Black hybrid thermal transfer ribbon. Use with heat shrink, self-laminating, Turn-Tell®, and vinyl cloth and tan polyimide labels.	4.33	110.0	1181.0	363.0	1
RHER4BL	Black resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RHER4WH	White resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RHER4BL-A	Black resin thermal transfer ribbon. Use with high-temperature marker plates.	4.33	110.0	1345.0	410.0	
RHER4BL-C	Black resin thermal transfer ribbon. Use with fluid resistant heat shrink markers and white polyimide labels.					
RHER4BL-E	Black resin thermal transfer ribbon. Used with standard marker plates and component labels for extra durability for harsh environments.					

Order number of ribbons required in multiples of Standard Package Quantity.



# PANDUIT®

Panduit Corp.  
World Headquarters  
Tinley Park, IL 60487

cs@panduit.com  
US and Canada: 800.777.3300  
Europe, Middle East, and Africa:  
44.20.8601.7200  
Latin America: 52.33.3777.6000  
Asia Pacific: 65.6305.7575

[www.panduit.com](http://www.panduit.com)