



NOTES: UNLESS OTHERWISE SPECIFIED.

1. SPECIFICATIONS:

1.1 FREQUENCY RANGE: DC - 26.5 GHz

1.2 VSWR (MAX):

DC - 4.0 GHz: 1.05:1

4.0 - 12.0 GHz: 1.10:1

12.0 - 18.0 GHz: 1.14:1

18.0 - 26.5 GHz: 1.30:1

1.3 MAXIMUM INPUT POWER:

2 WATTS MAX AT 25°C DERATED LINEARLY
TO 1 WATT AT 125°C.

1.4 IMPEDANCE: 50 OHMS NOMINAL

1.5 TEMPERATURE RANGE: -65°C TO 125°C

1.6 WEIGHT: .12 OZ (3.4 GRAMS) MAX.

1.7 FINISH: PASIVATED STAINLESS STEEL.

		Midwest Microwave	
	RoHS 2002/95/EC		
<small>This PROPRIETARY Document is property of Emerson Network Power Connectivity Solutions. It is confidential, non-transferable, and issued with the clear understanding that it is not tracked or copied without permission and is retrievable upon demand.</small>	<small>UNLESS OTHERWISE SPECIFIED</small> UNITS: INCH .XX ±.02 .XXX ±.005 ANGLES ±2°	Model No. TRM-2089-MC-SMA-02	
	<small>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</small>	Size A	DO NOT SCALE DRAWING
			Sheet 1 of 1